



Overview

Switching power supplies and UPS

Overview

Switching power supplies

| Series | up to 15.12 W | | | | | up to 26.4 W | | | | | up to 30 W | | | | | up to 36 W | | | | |
|----------|---------------|-----|-----|-----|-----|--------------|-----|-----|-----|-----|------------|-----|-----|-----|-----|------------|-----|-----|-----|-----|
| | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V |
| SPDE | | | | | | | | | | | | | | | | | | | | |
| SPDC | | | | | | | | | | | | | | | | | | | | |
| SPDM | | | | | | | | | | | | | | | | | | | | |
| SPD 2-ph | | | | | | | | | | | | | | | | | | | | |
| SPD 3-ph | | | | | | | | | | | | | | | | | | | | |
| SPPC | | | | | | ▼ | ▼ | | ▼ | | | | | | | ▼ | ▼ | | ▼ | |
| SPMA | ▼ | ▼ | ▼ | ▼ | | | ▼ | | | | | ▼ | | | | | | | | ▼ |

| Series | up to 100.8 W | | | | | 120 W | | | | | up to 151.2 W | | | | | up to 201.6 W | | | | | 240 W | | | | | |
|----------|---------------|-----|-----|-----|-----|-------|-----|-----|-----|-----|---------------|-----|-----|-----|-----|---------------|-----|-----|-----|-----|-------|-----|-----|-----|-----|---|
| | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | |
| SPDE | | | | | | | ▼ | | ▼ | ▼ | | | | | | | ▼ | | | | | | | | ▼ | ▼ |
| SPDC | | | | | | | ▼ | | ▼ | | | | | | | | | | | | | | | | ▼ | ▼ |
| SPDM | | | | | | | ▼ | | ▼ | ▼ | | | | | | | | | | | | | | | ▼ | ▼ |
| SPD 2-ph | | | | ▼ | | | | | | | | | | | | | | | | | | | | | ▼ | ▼ |
| SPD 3-ph | | | | | | | ▼ | | ▼ | | | | | | | | | | | | | | | | ▼ | ▼ |
| SPPC | | | | | | | | | | | | ▼ | | ▼ | | | ▼ | | ▼ | ▼ | | | | ▼ | ▼ | |
| SPMA | | | | ▼ | | | | | | | | | | | | | | | | | | | | | ▼ | ▼ |

SPDE series – Ultra compact power supply

The new generation of Carlo Gavazzi power supplies encompasses high performance within an extremely compact footprint, saving up to 50% space compared to similar devices. The SPDE comes in single phase input model types. It is extremely suitable for applications where high efficiency and

wide operating temperatures are required. The SPDE series consists of 3 frame sizes, starting from 75 W with 32 mm width, to maximum 480 W with 48 mm width. The high quality of these power supplies is certified by a series of industry approvals: CE, UKCA, UL61010, UL62368.



SPDM series – Medium compact power supply

This family of single phase input power supplies feature a reduced footprint, saving up to 30% space compared to similar devices. There are no frills, just standard features with high

performance and high reliability. The power rating ranges from 120 W to 240 W. The SPDM 120W comes with UL60950 and UL508.



SPDC series – Advanced compact power supply

This compact family achieves high performance in compact dimensions. It is ideal for critical installations where space and reliability are of utmost importance. The SPDC power boost can provide 150% of the rated output power for up to 3 seconds, to support

the extra power needed during critical start-ups. The parallel feature provides redundancy in times of breakdown. The SPDC comes with UL60950 and UL508.



| Series | Screw terminals | Parallel operation | Active current sharing | Power boost | Redundancy module | Battery charger / UPS |
|----------|-----------------|--------------------|------------------------|-------------|-------------------|-----------------------|
| SPDE | ▼ | | | ▼ | | |
| SPDC | ▼ | ▼ | | ▼ | | |
| SPDM | ▼ | | | | | |
| SPD 2-ph | ▼ | ▼ | ▼ | | | |
| SPD 3-ph | ▼ | ▼ | ▼ | | | |
| SPPC | ▼ | | | | | |
| SPMA | ▼ | | | | | |
| SPD RM | ▼ | | | | ▼ | |
| SPUBC | ▼ | ▼ | | ▼ | | ▼ |
| SPUC | ▼ | | | | | ▼ |
| SPM5BC | ▼ | | | | | ▼ |

Switching power supplies

| OUTPUT | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------|---------------|-----|-----|-----|-----|-------------|-----|-----|-----|-----|---------------|-----|-----|-----|-----|---------------|-----|-----|-----|-----|-------|-----|-----|-----|-----|
| Series | up to 54 W | | | | | 60 W | | | | | up to 76.8 W | | | | | up to 91.92 W | | | | | | | | | |
| | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | | | | | |
| SPDE | | | | | | | | | | | | ▼ | | ▼ | ▼ | | | | | | | | | | |
| SPDC | | | | | | | | | | | | | | | | | | | | | | | | | |
| SPDM | | | | | | | | | | | | | | | | | | | | | | | | | |
| SPD 2-ph | | | | | | | | | | | | | | | | | | | | | | | | | |
| SPD 3-ph | | | | | | | | | | | | | | | | | | | | | | | | | |
| SPPC | ▼ | ▼ | ▼ | ▼ | ▼ | ▼ | | | | | | | | ▼ | | ▼ | ▼ | | | | | | | | |
| SPMA | | ▼ | | | | | | ▼ | ▼ | | | | | | | | ▼ | ▼ | ▼ | | | | | | |
| Series | up to 321.6 W | | | | | up to 528 W | | | | | up to 652.8 W | | | | | 792 W | | | | | 960 W | | | | |
| | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V | 5V | 12V | 15V | 24V | 48V |
| SPDE | | | | | | | | | | | | | | | | | | | | | | | | | |
| SPDC | | | | | | | | | | ▼ | ▼ | | | | | | | | | | | | | | |
| SPDM | | | | | | | | | | ▼ | ▼ | | | | | | | | | | | | | | |
| SPD 2-ph | | | | | | | | | | | | | | | | | | | | | | | | | |
| SPD 3-ph | | | | | | | | | | | | | | | | | | | | | | | | | |
| SPPC | ▼ | | ▼ | ▼ | | ▼ | | | ▼ | ▼ | | | ▼ | | ▼ | ▼ | | | | | ▼ | ▼ | | | |
| SPMA | | | | | | | | | | | | | | | | | | | | | | | | | |



SPMA series - Low-profile DIN rail power supplies for building automation and electric car battery chargers

The SPMA series is a very compact DIN rail power supply designed for electrical panels with limited space. The SPMA series consists of 3 frame sizes, starting from 1 DIN (17.5 mm) for the 15 W to a maximum of 4 DIN

(70 mm) for the 100 W model. The low-profile design of SPMA makes it ideal for applications such as building automation and electrical vehicle charging stations as it is designed with 4 kVAC isolation voltage.



SPPC series - Enclosed type power supply

Enclosed metal casing power supplies are durable and economical, providing an excellent choice for customers, especially OEM machine makers, for any application. Power ratings range from 25 W to 800 W: in addition, the

SPPC comes with PFC from 100 W upwards. It comes with CE and UL approvals to cater to customers' requirements.



Battery chargers, UPS and Redundancy modules

Carlo Gavazzi provides the ideal selection of special devices for any critical applications. The Battery Chargers and UPS optimise the backup battery performance through controlled charging/discharging, while our advanced SPUBC integrates

a power supply, battery charger and UPS into a single unit. The Redundancy Modules guarantee the continuity of the DC supply to applications with zero downtime, enabling a consistent output even when a source is faulty.

| | cURus UL 60950-1 | cURus UL 62368-1 | cULus UL 508 | cULus UL 61010 | UL 1310 Class 2 | UL ISA 12.12.01 Class I Div2 | CE | UKCA |
|----------|---------------------|---------------------|-----------------|-------------------|--------------------|---------------------------------|----|------|
| SPDE | | Only 75 W | | ▼ | | | ▼ | ▼ |
| SPDC | ▼ | | ▼ | | | | ▼ | ▼ |
| SPDM | Only 120 W | | Only 120 W | | | | ▼ | ▼ |
| SPD 2-ph | ▼ | | ▼ | | | ▼ | ▼ | ▼ |
| SPD 3-ph | ▼ | | ▼ | | | ▼ | ▼ | ▼ |
| SPPC | ▼ | | | | | | ▼ | ▼ |
| SPMA | | ▼ | ▼ | | ▼ | ▼ | ▼ | ▼ |
| SPD RM | ▼ | | ▼ | | | | ▼ | ▼ |
| SPUBC | ▼ | | ▼ | | | | ▼ | ▼ |
| SPUC | | | ▼ | | | | ▼ | ▼ |
| SPM5BC | ▼ | | | | | | ▼ | ▼ |

Overview

Switching power supplies

SPDE Series - Single phase - DIN rail mounting



| Device | SPDE 75W | SPDE 120W | SPDE 120W R |
|-----------------------------|--|---|---|
| Output power | 75 W | 120 W | 120 W |
| Available output voltage DC | 12 V - 24 V - 48 V | 24 V | 12 V - 24 V - 48 V |
| Input AC | 90...264 V | 90...264 V | 90...264 V |
| Input DC | 120...370 V | 127...370 V | 127...370 V |
| Approvals | CE - UKCA - cULus - cURus | CE - UKCA - cULus | CE - UKCA - cULus |
| Dimensions | 87.5 x 32 x 129.80 mm (3.44" x 1.26" x 5.11") | 100 x 36 x 129.80 mm (3.94" x 1.42" x 5.11") | 110 x 32 x 128.82 mm (4.33" x 1.26" x 5.07") |
| Efficiency | 90% | 89% | 89% |
| DC ok | NO | NO | YES |

SPDE Series - Single phase - DIN rail mounting



| Device | SPDE 190W | SPDE 240W R | SPDE 480W R |
|-----------------------------|---|---|---|
| Output power | 190 W | 240 W | 480 W |
| Available output voltage DC | 12 V | 24 V - 48 V | 24 V - 48 V |
| Input AC | 85...264 V | 85...264 V | 85...264 V |
| Input DC | 120...370 V | 120...370 V | 120...370 V |
| Approvals | CE - UKCA - cULus | CE - UKCA - cULus | CE - UKCA - cULus |
| Dimensions | 110 x 41 x 128.82 mm (4.33" x 1.61" x 5.07") | 110 x 41 x 128.82 mm (4.33" x 1.61" x 5.07") | 131.5 x 48 x 130.60 mm (5.18" x 1.89" x 5.14") |
| Efficiency | 92,00% | 94,00% | 94,00% |
| DC ok | YES | YES | YES |

SPDC Series - Single phase - DIN Rail mounting



| Device | SPDC 120W | SPDC 240W | SPDC 480W |
|-----------------------------|--|--|--|
| Output power | 120 W | 240 W | 480 W |
| Available output voltage DC | 12 V - 24 V | 24 V | 24 V - 48 V |
| Input AC | 85...264 V | 85...264 V | 90...264 V |
| Input DC | 127...375 V | 127...375 V | 130...350 V |
| Approvals | CE - cULus - cURus | CE - cULus - cURus | CE - cULus - cURus |
| Dimensions | 124 x 119 x 32 mm (4.88" x 4.69" x 1.26") | 124 x 119 x 45 mm (4.88" x 4.69" x 1.77") | 124 x 127 x 70 mm (4.88" x 5.00" x 2.75") |
| Efficiency | 91% | 91% | 93% |
| DC ok | YES | YES | YES |

Switching power supplies

SPDM Series - Single phase - DIN Rail mounting



| Device | SPDM 120W | SPDM 240W |
|-----------------------------|--|--|
| Output power | 120 W | 240 W |
| Available output voltage DC | 12V - 24 V - 48 V | 24 V - 48 V |
| Input AC | 90...264 V | 90...264 V |
| Input DC | 127...375 V | 127...370 V |
| Approvals | CE - cULus - cURus | CE - cULus - cURus |
| Dimensions | 124 x 119 x 45 mm (4.88" x 4.69" x 1.77") | 124 x 127 x 70 mm (4.88" x 5.00" x 2.75") |
| Efficiency | 88% | 88% |
| DC ok | NO | NO |

SPD Series - Bi/Three phase - DIN rail mounting



| Device | SPD 100W/2 | SPD 120W/3 | SPD 240W/3 |
|-----------------------------|---|---|---|
| Output power | 100 W | 120 W | 240 W |
| Available output voltage DC | 24 V | 12 V - 24 V | 24 V - 48 V |
| Input AC | 340...575 V | 340...575 V | 340...575 V |
| Input DC | 340...820 V | 340...820 V | 340...820 V |
| Approvals | CE - UKCA - cULus - cURus - UL ISA 12.12.01 Class I Div2 | CE - UKCA - cULus - cURus - UL ISA 12.12.01 Class I Div2 | CE - UKCA - cULus - cURus - UL ISA 12.12.01 Class I Div2 |
| Dimensions | 90 x 54 x 114 mm (3.54" x 2.13" x 4.49") | 124 x 74.3 x 118.8 mm (4.88" x 2.92" x 4.68") | 124 x 89 x 118.8 mm (4.88" x 3.5" x 4.68") |
| Efficiency | 89% | 89% | 91% |
| DC ok | YES | YES | YES |

SPD Series - Bi/Three phase - DIN rail mounting



| Device | SPD 480W/3 | SPD 960W/3 |
|-----------------------------|---|---|
| Output power | 480 W | 960 W |
| Available output voltage DC | 24 V - 48 V | 24 V - 48 V |
| Input AC | 340...575 V | 340...575 V |
| Input DC | 340...820 V | 340...820 V |
| Approvals | CE - UKCA - cULus - cURus - UL ISA 12.12.01 Class I Div2 | CE - UKCA - cULus - cURus - UL ISA 12.12.01 Class I Div2 |
| Dimensions | 124 x 150 x 118.8 mm (4.88" x 5.91" x 4.68") | 126.2 x 275.8 x 118.8 mm (4.97" x 10.86" x 4.68") |
| Efficiency | 91% | 93% |
| DC ok | YES | YES |
| Options | | Without current sharing [L] |

Switching power supplies

SPPC Series - Single phase - Panel mounting



| Device | SPPC 25W | SPPC 35W | SPPC 50W | SPPC 75W |
|-----------------------------|---|---|--|---|
| Output power | 25...26.4W | 30...36 W | 40...53.76 W | 60...76.8 W |
| Available output voltage DC | 5 V - 12 V - 24 V | 5 V - 12 V - 24 V | 5 V - 12 V - 15 V - 24 V - 48 V | 5 V - 12 V - 24 V - 48 V |
| Input AC | 90...264 V | 90...264 V | 90...264 V | 90...264 V |
| Input DC | 127...370 V | 127...370 V | 127...370 V | 127...370 V |
| Approvals | CE - cURus | CE - cURus | CE - cURus | CE - cURus |
| Dimensions | 79 x 51 x 28.8 mm (3.11" x 2" x 1.13") | 101.6 x 63.5 x 33 mm (4" x 2.5" x 1.29") | 99 x 82 x 35 mm (3.89" x 3.22" x 1.37") | 129 x 98 x 39 mm (5.08" x 3.85" x 1.53") |
| Efficiency | 85% | 87% | 89% | 89% |

SPPC Series - Single phase - Panel mounting



| Device | SPPC 150W | SPPC 200W | SPPC 240W |
|-----------------------------|---|---|---|
| Output power | 150...151.2 W | 200...201.6 W | 240 W |
| Available output voltage DC | 12 V - 24 V | 5 V - 12 V - 24 V - 48 V | 12 V - 24 V |
| Input AC | 86...264 V | 85...264 V | 85...264 V |
| Input DC | 120...370 V | 120...370 V | 120...370 V |
| Approvals | CE - cURus | CE - cURus | CE - cURus |
| Dimensions | 160 x 98 x 38 mm (6.29" x 3.85" x 1.49") | 199 x 99 x 50 mm (7.83" x 3.89" x 1.96") | 199 x 99 x 50 mm (7.83" x 3.89" x 1.96") |
| Efficiency | 87% | 87% | 86% |
| Features | Compact, PFC | Compact, PFC | Compact, PFC |

SPPC Series - Single phase - Panel mounting



| Device | SPPC 320W | SPPC 480W | SPPC 600W | SPPC 800W |
|-----------------------------|---|--|--|--|
| Output power | 275...321.6 W | 408...528 W | 504...652.8 W | 792 W |
| Available output voltage DC | 5 V - 12 V - 24 V - 48 V | 12V - 24V - 36V - 48V | 12 V - 24 V - 36 V - 48 V | 24 V - 48 V |
| Input AC | 85...264 V | 90...264 V | 90...264 V | 90...264 V |
| Input DC | 120...370 V | 127...370 V | 127...370 V | 127...370 V |
| Approvals | CE - cURus | CE - cURus | CE - cURus | CE - cURus |
| Dimensions | 199 x 99 x 50 mm (7.83" x 3.89" x 1.96") | 226 x 116.5 x 41 mm (8.89" x 4.58" x 1.61") | 226 x 116.5 x 41 mm (8.89" x 4.58" x 1.61") | 226 x 116.5 x 41 mm (8.89" x 4.58" x 1.61") |
| Efficiency | 87% | 90% | 90% | 90% |
| Features | Compact, PFC | Compact, PFC | Compact, PFC | Compact, PFC |

Switching power supplies

SPMA Series - Single phase - DIN rail mounting



| Device | SPMA 15 | SPMA 30 | SPMA 60 | SPMA 100 |
|-----------------------------|---|---|---|---|
| Output power | 12...15 W | 25...36 W | 54...60 W | 85...100 W |
| Available output voltage DC | 5 V - 12 V - 15 V - 24 V | 5 V - 12 V - 15 V - 24 V | 12 V - 15 V - 24 V | 12 V - 15 V - 24 V |
| Input AC | 85...264 V | 85...264 V | 85...264 V | 85...264 V |
| Input DC | 120...350 V | 120...350 V | 120...350 V | 120...350 V |
| Approvals | CE - UKCA - cULus - cURus - UL1310 Class 2 - UL ISA 12.12.01 Class I Div2 | CE - UKCA - cULus - cURus - UL1310 Class 2 - UL ISA 12.12.01 Class I Div2 | CE - UKCA - cULus - cURus - UL1310 Class 2 - UL ISA 12.12.01 Class I Div2 | CE - UKCA - cULus - cURus - UL1310 Class 2 - UL ISA 12.12.01 Class I Div2 |
| Dimensions | 91 x 18 x 63 mm (3.58" x 0.71" x 2.48") | 91 x 52.5 x 63 mm (3.58" x 2.07" x 2.48") | 91 x 52.5 x 63 mm (3.58" x 2.07" x 2.48") | 91 x 70 x 63 mm (3.58" x 2.76" x 2.48") |
| Efficiency | 85% | 88% | 89% | 89% |
| DC ok (LED indication) | YES | YES | YES | YES |
| Options | Conformal coating [SCC] | Conformal coating [SCC] | Conformal coating [SCC] | Conformal coating [SCC] |

Battery chargers & UPS



| Device | SPUBC UPS battery charger | SPUC UPS controller | SPM5 Battery charger |
|-----------------------------|--|---|--|
| Output power | 120 W | 360 W - 720 W | 30 W - 60 W |
| Available output voltage DC | 12 V - 24 V | 12 V - 24 V | 12 V - 24 V |
| Input AC | 115...277 V | | 90...264 V |
| Input DC | | 11...14 V - 22...28 V | |
| Approvals | CE - UKCA - cURus | CE - UKCA - cULus - cURus | CE - UKCA |
| Dimensions | 65 x 115 x 135 mm (2.56" x 4.53" x 5.31") | 90 x 54 x 114 mm (3.54" x 2.13" x 4.49") | 91 x 90 x 57 mm (3.58" x 3.54" x 2.24") |
| Mounting | DIN rail | DIN rail | DIN rail |

DIN-rail battery bank

Redundancy modules



| Device | SPUBAT24 | SPD RM |
|-----------------------------|---|---|
| Output current | 1.2 A - 3.2 A - 7.2 A - 12 A | 20 A |
| Available output voltage DC | DC 24 V | 24 V |
| Input DC | 24 V | 21...28 V |
| Approvals | CE | CE - UKCA - cULus - cURus |
| Dimensions | SPUBAT241A2: 176 x 67 x 122 mm (6.93" x 2.64" x 4.8") SPUBAT243A2: 193 x 75 x 163 mm (7.59" x 2.95" x 6.42") SPUBAT247A2: 203 x 139 x 129 mm (7.99" x 5.47" x 5.08") SPUBAT2412A: 201 x 114 x 205 mm (7.91" x 4.49" x 8.07") | 90 x 54 x 114 mm (3.54" x 2.13" x 4.49") |
| Mounting | DIN rail | DIN rail |

OUR SALES NETWORK IN EUROPE

AUSTRIA

Carlo Gavazzi GmbH
Ketzergasse 374,
A-1230 Wien
Tel: +43 1 888 4112
Fax: +43 1 889 1053
office@carlogavazzi.at

FRANCE

Carlo Gavazzi Sarl
Zac de Paris Nord II, 69, rue de la Belle Etoile,
F-95956 Roissy CDG Cedex
Tel: +33 1 49 38 98 60
Fax: +33 1 48 63 27 43
french.team@carlogavazzi.fr

ITALY

Carlo Gavazzi SpA
Via Milano, 13,
I-20045 Lainate
Tel: +39 02 931 76 1
Fax: +39 02 931 76 301
info@gavazziacbu.it

SPAIN

Carlo Gavazzi SA
Avda. Iparraguirre, 80-82,
E-48940 Leioa (Bizkaia)
Tel: +34 94 480 40 37
Fax: +34 94 431 60 81
gavazzi@gavazzi.es

BELGIUM

Carlo Gavazzi NV/SA
Mechelsesteenweg 311,
B-1800 Vilvoorde
Tel: +32 2 257 41 20
sales@carlogavazzi.be

GERMANY

Carlo Gavazzi GmbH
Pfnorstr. 10-14
D-64293 Darmstadt
Tel: +49 6151 81 00 0
Fax: +49 6151 81 00 40
info@gavazzi.de

NETHERLANDS

Carlo Gavazzi BV
Wijkemeerweg 23,
NL-1948 NT Beverwijk
Tel: +31 251 22 93 45
Fax: +31 251 22 60 55
info@carlogavazzi.nl

SWEDEN

Carlo Gavazzi AB
V:a Kyrkogatan 1,
S-652 24 Karlstad
Tel: +46 54 85 11 25
Fax: +46 54 85 11 77
info@carlogavazzi.se

DENMARK

Carlo Gavazzi Handel A/S
Over Hadstenevej 40,
DK-8370 Hadsten
Tel: +45 89 60 61 00
Fax: +45 86 98 15 30
handel@gavazzi.dk

GREAT BRITAIN

Carlo Gavazzi UK Ltd
4.4 Frimley Business Park,
Frimley, Camberley, Surrey GU16 7SG
Tel: +44 1 276 854110
Fax: +44 1 276 682140
sales@carlogavazzi.co.uk

NORWAY

Carlo Gavazzi AS
Melkeveien 13,
N-3919 Parsgrunn
Tel: +47 35 93 08 00
Fax: +47 35 93 08 01
post@gavazzi.no

SWITZERLAND

Carlo Gavazzi AG
Verkauf Schweiz/Vente Suisse
Sumpfstrasse 3,
CH-6312 Steinhausen
Tel: +41 41 747 45 35
Fax: +41 41 740 45 40
info@carlogavazzi.ch

FINLAND

Carlo Gavazzi OY AB
Ahventie, 4 B
FI-02170 Espoo
Tel: +358 9 756 2000
myynti@gavazzi.fi

PORTUGAL

Carlo Gavazzi Lda
Rua dos Jerónimos 38-B,
P-1400-212 Lisboa
Tel: +351 21 361 70 60
Fax: +351 21 362 13 73
carlogavazzi@carlogavazzi.pt

OUR SALES NETWORK IN THE AMERICAS

USA

Carlo Gavazzi Inc.
750 Hastings Lane,
Buffalo Grove, IL 60089-6904, USA
Tel: +1 847 465 61 00
Fax: +1 847 465 73 73
sales@carlogavazzi.com

CANADA

Carlo Gavazzi Inc.
2660 Meadowvale Boulevard,
Mississauga, ON L5N 6M6, Canada
Tel: +1 905 542 0979
Fax: +1 905 542 2248
gavazzi@carlogavazzi.com

MEXICO

Carlo Gavazzi Mexico S.A. de C.V.
Circuito Puericultores 22, Ciudad Satelite
Naucalpan de Juárez, Edo Mex. CP 53100
Mexico
T +52 55 5373 7042
F +52 55 5373 7042
mexicosales@carlogavazzi.com

BRAZIL

Carlo Gavazzi Automação Ltda.
Av. Francisco Matarazzo, 1752
Conj 2108 05001-200 - São Paulo - SP
Tel: +55 11 3052 0832
Fax: +55 11 3057 1753
info@carlogavazzi.com.br

OUR SALES NETWORK IN ASIA AND PACIFIC

SINGAPORE

Carlo Gavazzi Automation Singapore Pte. Ltd.
61 Tai Seng Avenue #05-06
Print Media Hub @ Paya Lebar iPark
Singapore 534167
Tel: +65 67 466 990
Fax: +65 67 461 980
info@carlogavazzi.com.sg

MALAYSIA

Carlo Gavazzi Automation (M) SDN. BHD.
D12-06-G, Block D12,
Pusat Perdagangan Dana 1,
Jalan PJU 1A/46, 47301 - Petaling Jaya,
Selangor, Malaysia
Tel: +60 3 7842 7299
Fax: +60 3 7842 7399
info@gavazzi-asia.com

CHINA

Carlo Gavazzi Automation
(China) Co. Ltd.
Unit 2308, 23/F.,
News Building, Block 1, 1002
Middle Shennan Zhong Road, Futian District,
Shenzhen, China
Tel: +86 755 8369 9500
Fax: +86 755 8369 9300
sales@carlogavazzi.cn

HONG KONG

Carlo Gavazzi Automation
Hong Kong Ltd.
Unit No. 16 on 25th Floor, One Midtown,
No. 11 Hoi Shing Road, Tsuen Wan,
New Territories, Hong Kong
Tel: +852 26261332 / 26261333
Fax: +852 26261316

TAIWAN

Branch of Carlo Gavazzi Automation
Singapore Pte. Ltd.
22F-1, No.500 Shizheng Rd, Xitun Dist,
Taichung City 407,
Taiwan, China
Tel: +886 4 2258 4001
Fax: +886 4 2258 4002

OUR COMPETENCE CENTRES AND PRODUCTION SITES

DENMARK

Carlo Gavazzi Industri A/S
Hadsten

MALTA

Carlo Gavazzi Ltd
Zejtun

ITALY

Carlo Gavazzi Controls SpA
Belluno

LITHUANIA

Uab Carlo Gavazzi Industri Kaunas
Kaunas

CHINA

Carlo Gavazzi Automation (Kunshan) Co., Ltd.
Kunshan

HEADQUARTERS

Carlo Gavazzi Automation SpA
Via Milano, 13
I-20045 - Lainate (MI) - ITALY
Tel: +39 02 931 76 1
info@gavazziautomation.com

Energy to Components!

www.gavazziautomation.com