



Overview

Switching power supplies and UPS

Overview


Switching power supplies

OUTPUT																				
Series	up to 15.12 W					up to 26.4 W					up to 30 W					up to 36 W				
	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V
SPDL		▼		▼								▼		▼						
SPDC																				
SPDM												▼		▼						
SPD	▼	▼	▼	▼							▼	▼		▼	▼					
SPD 2-ph																				
SPD 3-ph																				
SPPC						▼	▼		▼							▼	▼		▼	
SPMA	▼	▼	▼	▼			▼		▼		▼			▼						▼

Series	up to 100.8 W					120 W					up to 151.2 W					up to 201.6 W					240 W				
	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V
SPDL										▼															▼
SPDC							▼		▼																▼
SPDM							▼		▼	▼															▼
SPD	▼		▼	▼		▼			▼	▼															▼
SPD 2-ph				▼																					▼
SPD 3-ph						▼			▼							▼	▼		▼	▼					▼
SPPC											▼	▼				▼	▼		▼	▼					▼
SPMA				▼																					▼

SPDL series – Ultra compact power supply

This new series of power supplies encompasses high performance within an extremely compact footprint, saving up to 75% space compared to similar devices. The SPDL comes in single phase input model types. It is suitable for applications where high efficiency and wide operating temperatures are required. The SPDL series consists of 3 frame sizes, plastic housing for 15, 30 and 60 W with 32mm width, metal housing for 120 and 240 W with 32mm width, and 480 W with 45mm width. The high quality of these power supplies is certified by a series of industry approvals: CE, UL61010, UL62368.



SPDC series – Advanced compact power supply

This compact family achieves high performance in compact dimensions. It is ideal for critical installations where space and reliability are of utmost importance. The SPDC power boost can provide 150% of the rated output power for up to 3 seconds, to support the extra power needed during critical start-ups. The parallel feature provides redundancy in times of breakdown. The SPDC comes with CE, UL60950, UL62368 and UL508.



SPDM series – Medium compact power supply

This family of single phase input power supplies feature a reduced footprint, saving up to 30% space compared to similar devices. There are no frills, just standard features with high performance and high reliability. The power rating ranges is 30, 50, 75 W for plastic housing, and 120, 240 W for metal housing. The SPDM 120W comes with CE, UL60950, UL62368 and UL508.



SPD series – General purpose power supply

The first generation of Carlo Gavazzi power supplies have the greatest range of power ratings available and the highest number of approvals for most industrial applications. The SPD comes in single phase input, two phase input, and three phase input model types. It is suitable for demanding applications where dimensions are not an issue; from harsh environments with ISA Class 1 Division 2 to safety low voltage with UL1310 Class 2 approvals (<90 W).



Series	Screw terminals	Spring terminals	Parallel operation	Active current sharing	Power boost	Battery charger / UPS
SPDL	▼					
SPDC	▼		▼		▼	
SPDM	▼	▼				
SPD	▼		▼	▼		
SPD 2-ph	▼		▼	▼		
SPD 3-ph	▼		▼	▼		
SPPC	▼					
SPMA	▼					
SPUBC	▼		▼		▼	▼

Switching power supplies

OUTPUT																				
Series	up to 54 W					60 W					up to 76.8 W					up to 91.92 W				
	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V
SPDL																				
SPDC																				
SPDM		▼		▼																
SPD						▼	▼			▼	▼									▼
SPD 2-ph																				
SPD 3-ph																				
SPPC	▼	▼	▼	▼	▼	▼									▼	▼	▼			
SPMA		▼						▼	▼									▼	▼	▼

Series	up to 321.6 W					up to 528 W					up to 652.8 W					792 W					960 W				
	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V	5V	12V	15V	24V	48V
SPDL																									
SPDC																									
SPDM																									
SPD				▼	▼					▼	▼														
SPD 2-ph																									
SPD 3-ph																								▼	▼
SPPC	▼		▼	▼		▼				▼	▼			▼	▼					▼	▼				
SPMA																									



SPPC series – Enclosed type power supply

Enclosed metal casing power supplies are durable and economical, providing an excellent choice for customers, especially OEM machine makers, for any application. Power ratings range from 25 W to 800 W: in addition, the SPPC comes with PFC from 100 W upwards. It comes with CE and UL approvals to cater to customers' requirements.



SPMA series - Low-profile DIN rail power supplies for building automation and electric car battery chargers

The SPMA series is a very compact DIN rail power supply designed for electrical panels with limited space. The SPMA series consists of 3 frame sizes, starting from 1 DIN (17.5 mm) for the 15 W to a maximum of 4 DIN (70 mm) for the 100 W model. The low-profile design of SPMA makes it ideal for applications such as building automation and electrical vehicle charging stations as it is designed with 4 kVAC isolation voltage.



Battery chargers, UPS and Redundancy modules

Carlo Gavazzi provides the ideal selection of special devices for any critical applications. The Battery Chargers and UPS optimise the backup battery performance through controlled charging/discharging, while our advanced SPUBC integrates a power supply, battery charger and UPS into a single unit. The Redundancy Modules guarantee the continuity of the DC supply to applications with zero downtime, enabling a consistent output even when a source is faulty.

	cURus UL 60950-1	cURus UL 62368-1	cULus UL 508	cULus UL 61010	UL 1310 Class 2	UL ISA 12.12.01 Class I Div2	CE	UKCA
SPDL		▼		▼			▼	
SPDC	▼		▼				▼	
SPDM	▼	▼	▼				▼	
SPD	▼		▼		▼	▼	▼	▼
SPD 2-ph	▼		▼			▼	▼	▼
SPD 3-ph	▼		▼			▼	▼	▼
SPPC	▼						▼	
SPMA		▼	▼		▼	▼	▼	▼
SPUBC	▼	▼	▼				▼	▼

Overview

Switching power supplies

SPDL Series - Single phase - DIN rail mounting



Device	SPDL 15...60W	SPDL 75W	SPDL 120W	SPDL 240W R	SPDL 480W / 480W R
Output power	15 W	15 W	120 W	240 W	480 W
Available output voltage DC	12 V - 24 V	12 V - 24 V	24 V	24 V	24 V - 48 V
Input AC	90...264 V	90...264 V	90...264 V	85...264 V	85/90...264 V
Input DC	127...370 V (120...370 V 15 W)	127...370 V	120...370 V	120...370 V	120/127...375 V
Approvals	CE - cURus	CE - cULus	CE - cULus	CE - cULus	CE - cULus
Dimensions	97.6 x 32 x 103.70 mm (3.84" x 1.26" x 4.08")	124 x 32 x 119 mm (4.88" x 1.26" x 4.68")	124 x 32 x 119 mm (4.88" x 1.26" x 4.68")	124 x 32 x 119 mm (4.88" x 1.26" x 4.68")	124 x 45 x 119 mm (5.11" x 1.77" x 4.68")
Efficiency	84.5...88%	84.5...88%	88.5%	95,00%	94...95%
DC ok	NO	NO	NO	YES	YES (480 R)

SPDC Series - Single phase - DIN Rail mounting



Device	SPDC 120W	SPDC 240W	SPDC 480W
Output power	120 W	240 W	480 W
Available output voltage DC	12 V - 24 V	24 V	24 V - 48 V
Input AC	85...264 V	85...264 V	90...264 V
Input DC	127...375 V	127...375 V	130...350 V
Approvals	CE - cULus - cURus	CE - cULus - cURus	CE - cULus - cURus
Dimensions	124 x 119 x 32 mm (4.88" x 4.69" x 1.26")	124 x 119 x 45 mm (4.88" x 4.69" x 1.77")	124 x 127 x 70 mm (4.88" x 5.00" x 2.75")
Efficiency	91,00%	91,00%	93,00%
DC ok	YES	YES	YES

SPDM Series - Single phase - DIN Rail mounting



Device	SPDM 30	SPDM 50	SPDM 75	SPDM 120W	SPDM 240W
Output power	24 W - 30 W	48 W - 50 W	66 W - 72 W	120 W	240 W
Available output voltage DC	12 V - 24 V	12 V - 24 V	12 V - 24 V	12V - 24 V - 48 V	24 V - 48 V
Input AC	85...264 V	85...264 V	85...264 V	90...264 V	90...264 V
Input DC	120...375 V	120...375 V	120...375 V	127...370 V	127...370 V
Approvals	CE - TÜV - cULus - UL 1310 Cl. 2	CE - TÜV - cULus - UL 1310 Cl. 2	CE - TÜV - cULus - UL1310 Cl. 2 (only for 24 VDC)	CE - cULus - cURus	CE
Dimensions	90 x 100 x 22.5 mm (3.54" x 3.937" x 0.885")	90 x 100 x 30 mm (3.54" x 3.937" x 1.181")	90 x 100 x 40.5 mm (3.54" x 3.937" x 1.594")	124 x 119 x 45 mm (4.88" x 4.69" x 1.77")	124 x 127 x 70 mm (4.88" x 5.00" x 2.75")
Efficiency	86,00%	87,00%	87,00%	88,00%	88,00%
DC ok	NO	NO	NO	NO	NO
Options	Spring terminal [B]	Spring terminal [B]	Spring terminal [B]		

Switching power supplies

SPD Series - single phase - DIN rail mounting



Device	SPD 5W	SPD 10W	SPD 18W	SPD 30W
Output power	5 W	10 W	18 W	30 W
Available output voltage DC	5 V - 12V - 15 V - 24 V	5 V - 12V - 15 V - 24 V	5 V - 12V - 15 V - 24 V	5 V - 12V - 15 V - 24 V
Input AC	90...264 V	90...264 V	90...264 V	90...264 V
Input DC	120...370 V	120...375 V	120...375 V	90...375 V
Approvals	CE - TÜV - cULus - UL 1310 Cl. 2 - Class I Div. 2	CE - TÜV - cULus - UL 1310 Cl. 2 - Class I Div. 2	CE - TÜV - cULus - UL 1310 Cl. 2 - Class I Div. 2	CE - TÜV - cULus - UL 1310 Cl. 2 - Class I Div. 2
Dimensions	90 x 22.5 x 114 mm (3.54" x 0.89" x 4.49")	90 x 22.5 x 114 mm (3.54" x 0.89" x 4.49")	90 x 22.5 x 114 mm (3.54" x 0.89" x 4.49")	90 x 22.5 x 114 mm (3.54" x 0.89" x 4.49")
Efficiency	87%	76%	77%	86%
DC ok	NO	NO	NO	YES
Options		Spring terminal [B]	Spring terminal [B]	Spring terminal [B]

SPD Series - single phase - DIN rail mounting



Device	SPD 60W	SPD 90W	SPD 100W
Output power	60 W	90 W	100 W
Available output voltage DC	5 V - 12V - 24 V - 48 V	24 V	24 V
Input AC	85...264 V	90...264 V	90...264 V
Input DC	90...375 V	120...375 V	120...375 V
Approvals	CE - TÜV - cULus - UL 1310 Cl. 2 - Class I Div. 2	CE - TÜV - cULus - UL 1310 Cl. 2 - Class I Div. 2	CE - TÜV - cULus - UL 1310 Cl. 2 - Class I Div. 2
Dimensions	90 x 40.5 x 114 mm (3.54" x 1.59" x 4.49")	90 x 54 x 114 mm (3.54" x 2.13" x 4.49")	90 x 54 x 114 mm (3.54" x 2.13" x 4.49")
Efficiency	89%	86%	88%
DC ok	YES	YES	YES
Options	Spring terminal [B]	Plastic housing [L]	




SPD Series - single phase - DIN rail mounting



Device	SPD 120W	SPD 240W	SPD 300W	SPD 480W
Output power	120 W	240 W	300 W	480 W
Available output voltage DC	12 V - 24 V	12 V - 24 V - 48 V	24 V - 48 V	24 V - 48 V
Input AC	90...264 V	90...264 V	90...264 V	90...264 V
Input DC	210...315 V	120...375 V	120...375 V	120...375 V
Approvals	CE - TÜV - cULus - Class I Div. 2	CE - TÜV - cULus - Class I Div. 2	CE - TÜV - cULus - Class I Div. 2	CE - TÜV - cULus - Class I Div. 2
Dimensions	90 x 22.5 x 114 mm (3.54" x 0.89" x 4.49")	90 x 22.5 x 114 mm (3.54" x 0.89" x 4.49")	90 x 22.5 x 114 mm (3.54" x 0.89" x 4.49")	90 x 22.5 x 114 mm (3.54" x 0.89" x 4.49")
Efficiency	87%	90%	90%	90%
DC ok	YES	YES	YES	YES
Options		Detachable terminals [B]		Detachable terminals [B]


Switching power supplies

SPPC Series - Single phase - Panel mounting



Device	SPPC 25W	SPPC 35W	SPPC 50W	SPPC 75W
Output power	25...26.4W	30...36 W	40...53.76 W	60...76.8 W
Available output voltage DC	5 V - 12 V - 24 V	5 V - 12 V - 24 V	5 V - 12 V - 15 V - 24 V - 48 V	5 V - 12 V - 24 V - 48 V
Input AC	90...264 V	90...264 V	90...264 V	90...264 V
Input DC	127...370 V	127...370 V	127...370 V	127...370 V
Approvals	CE - cURus	CE - cURus	CE - cURus	CE - cURus
Dimensions	79 x 51 x 28.8 mm (3.11" x 2" x 1.13")	101.6 x 63.5 x 33 mm (4" x 2.5" x 1.29")	99 x 82 x 35 mm (3.89" x 3.22" x 1.37")	129 x 98 x 39 mm (5.08" x 3.85" x 1.53")
Efficiency	85%	87%	89%	89%

SPPC Series - Single phase - Panel mounting



Device	SPPC 150W	SPPC 200W	SPPC 240W
Output power	150...151.2 W	200...201.6 W	240 W
Available output voltage DC	12 V - 24 V	5 V - 12 V - 24 V - 48 V	12 V - 24 V
Input AC	86...264 V	85...264 V	85...264 V
Input DC	120...370 V	120...370 V	120...370 V
Approvals	CE - cURus	CE - cURus	CE - cURus
Dimensions	160 x 98 x 38 mm (6.29" x 3.85" x 1.49")	199 x 99 x 50 mm (7.83" x 3.89" x 1.96")	199 x 99 x 50 mm (7.83" x 3.89" x 1.96")
Efficiency	87%	87%	86%
Features	Compact, PFC	Compact, PFC	Compact, PFC

SPPC Series - Single phase - Panel mounting



Device	SPPC 320W	SPPC 480W	SPPC 600W	SPPC 800W
Output power	275...321.6 W	408...528 W	504...652.8 W	792 W
Available output voltage DC	5 V - 12 V - 24 V - 48 V	12V - 24V - 36V - 48V	12 V - 24 V - 36 V - 48 V	24 V - 48 V
Input AC	85...264 V	90...264 V	90...264 V	90...264 V
Input DC	120...370 V	127...370 V	127...370 V	127...370 V
Approvals	CE - cURus	CE - cURus	CE - cURus	CE - cURus
Dimensions	199 x 99 x 50 mm (7.83" x 3.89" x 1.96")	226 x 116.5 x 41 mm (8.89" x 4.58" x 1.61")	226 x 116.5 x 41 mm (8.89" x 4.58" x 1.61")	226 x 116.5 x 41 mm (8.89" x 4.58" x 1.61")
Efficiency	87%	90%	90%	90%
Features	Compact, PFC	Compact, PFC	Compact, PFC	Compact, PFC

Switching power supplies

SPD Series - Bi/Three phase - DIN rail mounting



Device	SPD 100W/2	SPD 120W/3	SPD 240W/3	SPD 480W/3	SPD 960W/3
Output power	100 W	120 W	240 W	480 W	960 W
Available output voltage DC	24 V	12 V - 24 V	24 V - 48 V	24 V - 48 V	24 V - 48 V
Input AC	340...575 V	340...575 V	340...575 V	340...575 V	340...575 V
Input DC	340...820 V	340...820 V	340...820 V	340...820 V	340...820 V
Approvals	CE - TÜV - cULus - Class I Div 2	CE - TÜV - cULus - Class I Div 2	CE - TÜV - cULus - Class I Div 2	CE - TÜV - cULus - Class I Div 2	CE - TÜV - cULus - Class I Div 2
Dimensions	90 x 54 x 14.4 mm (3.6" x 2.13" x 4.49")	124 x 74.3 x 118.8 mm (4.88" x 2.92" x 4.68")	124 x 89. x 118.8 mm (4.88" x 3.5" x 4.68")	124 x 150 x 118.8 mm (4.88" x 5.91" x 4.68")	126.2 x 275.8 x 118.8 mm (4.97" x 10.86" x 4.68")
Efficiency	89,00%	89,00%	91,00%	91,00%	93,00%
DC ok	YES	YES	YES	YES	YES
Options					Without current sharing [L]

SPMA Series - Single phase - DIN rail mounting



Device	SPMA 15	SPMA 30	SPMA 60	SPMA 100
Output power	12...15 W	25...36 W	54...60 W	85...100 W
Available output voltage DC	5 V - 12 V - 15 V - 24 V	5 V - 12 V - 15 V - 24 V	12 V - 15 V - 24 V	12 V - 15 V - 24 V
Input AC	85...264 V	85...264 V	85...264 V	85...264 V
Input DC	120...350 V	120...350 V	120...350 V	120...350 V
Approvals	CE - UKCA - cULus - cURus - UL1310 Class 2 - UL ISA 12.12.01 Class I Div2	CE - UKCA - cULus - cURus - UL1310 Class 2 - UL ISA 12.12.01 Class I Div2	CE - UKCA - cULus - cURus - UL1310 Class 2 - UL ISA 12.12.01 Class I Div2	CE - UKCA - cULus - cURus - UL1310 Class 2 - UL ISA 12.12.01 Class I Div2
Dimensions	91 x 18 x 63 mm (3.58" x 0.71" x 2.48")	91 x 52.5 x 63 mm (3.58" x 2.07" x 2.48")	91 x 52.5 x 63 mm (3.58" x 2.07" x 2.48")	91 x 70 x 63 mm (3.58" x 2.76" x 2.48")
Efficiency	85%	88%	89%	89%
DC ok (LED indication)	YES	YES	YES	YES
Options	Conformal coating [SCC]	Conformal coating [SCC]	Conformal coating [SCC]	Conformal coating [SCC]

Battery chargers & UPS

DIN rail battery bank



Device	SPUBC UPS battery charger	SPUBAT24
Output current	120 W	1.2 A - 3.2 A - 7.2 A - 12 A
Available output voltage DC	12 V - 24 V	DC 24 V
Input AC	115...277 V	
Input DC		24 V
Approvals	CE - UKCA - cURus	CE
Dimensions	65 x 115 x 135 mm (2.56" x 4.53" x 5.31")	SPUBAT241A2: 176 x 67 x 122 mm (6.93" x 2.64" x 4.80") SPUBAT243A2: 193 x 75 x 163 mm (7.59" x 2.95" x 6.42") SPUBAT247A2: 203 x 139 x 129 mm (7.99" x 5.47" x 5.08") SPUBAT2412A: 201 x 114 x 205 mm (7.91" x 4.49" x 8.07")
Mounting	DIN rail	DIN rail

OUR SALES NETWORK IN EUROPE

AUSTRIA

Carlo Gavazzi GmbH
Ketzergasse 374,
A-1230 Wien
Tel. +43 1 888 4112
Fax +43 1 889 1053
office@carlogavazzi.at

FINLAND

Carlo Gavazzi OY AB
Ahventie, 4 B
FI-02170 Espoo
Tel. +358 9 756 2000
myynti@gavazzi.fi

GREAT BRITAIN

Carlo Gavazzi UK Ltd
4.4 Frimley Business Park,
Frimley, Camberley,
Surrey GU16 7SG
Tel. +44 1 276 854110
sales@carlogavazzi.co.uk

NORWAY

Carlo Gavazzi AS
Melkeveien 13,
N-3919 Porsgrunn
Tel. +47 35 93 08 00
post@gavazzi.no

SWEDEN

Carlo Gavazzi AB
V:a Kyrkogatan 1,
S-652 24 Karlstad
Tel. +46 54 85 11 25
Fax +46 54 85 11 77
info@carlogavazzi.se

BELGIUM

Carlo Gavazzi NV/SA
Mechelsesteenweg 311,
B-1800 Vilvoorde
Tel. +32 2 257 41 20
sales@carlogavazzi.be

FRANCE

Carlo Gavazzi Sarl
Zac de Paris Nord II, 69,
rue de la Belle Etoile,
F-95956 Roissy CDG Cedex
Tel. +33 1 49 38 98 60
Fax +33 1 48 63 27 43
french.team@carlogavazzi.fr

ITALY

Carlo Gavazzi SpA
Via Milano 13,
I-20045 Lainate (MI)
Tel. +39 02 931 76 1
info@gavazziacbu.it

PORTUGAL

Carlo Gavazzi Lda
Rua das Jerónimos 38-B,
P-1400-212 Lisboa
Tel. +351 21 361 70 60
Fax +351 21 362 13 73
carlogavazzi@carlogavazzi.pt

SWITZERLAND

Carlo Gavazzi AG
Verkauf Schweiz/Vente Suisse
Sumpfstrasse 3,
CH-6312 Steinhausen
Tel. +41 41 747 45 35
Fax +41 41 740 45 40
info@carlogavazzi.ch

DENMARK

Carlo Gavazzi Handel A/S
Over Hadstenvej 40,
DK-8370 Hadsten
Tel. +45 89 60 61 00
Fax +45 86 98 15 30
handel@gavazzi.dk

GERMANY

Carlo Gavazzi GmbH
Pforstr. 10-14
D-64293 Darmstadt
Tel. +49 6151 81 00 0
Fax +49 6151 81 00 40
info@gavazzi.de

NETHERLANDS

Carlo Gavazzi BV
Wijkmeerweg 23,
NL-1948 NT Beverwijk
Tel. +31 251 22 93 45
info@carlogavazzi.nl

SPAIN

Carlo Gavazzi SA
Avda. Iparraguirre, 80-82,
E-48940 Leioa (Bizkaia)
Tel. +34 94 480 40 37
Fax +34 94 431 60 81
gavazzi@gavazzi.es

OUR SALES NETWORK IN THE AMERICAS

USA

Carlo Gavazzi Inc.
750 Hastings Lane,
Buffalo Grove, IL 60089-6904,
USA
Tel. +1 847 465 61 00
sales@carlogavazzi.com

CANADA

Carlo Gavazzi Inc.
2430 Meadowpine Blvd Unit
104
Mississauga, ON L5N 6S2,
Canada
Tel. +1 905 542 0979
gavazzi@carlogavazzi.com

MEXICO

Carlo Gavazzi Mexico S.A. de C.V.
Circuito Puericultores 22,
Ciudad Satelite
Naucalpan de Juárez,
Edo Mex. CP 53100 - Mexico
Tel. +52 55 5373 7042
Fax +52 55 5373 7042
mexicosales@carlogavazzi.com

BRAZIL

Carlo Gavazzi Automação Ltda.
Av. Francisco Matarazzo,
1752 Conjunto 2108
CEP 05001-200 -
São Paulo - SP - Brazil
Tel. +55 11 3052 0832
Fax +55 11 3057 1753
info@carlogavazzi.com.br

OUR SALES NETWORK IN ASIA AND PACIFIC

SINGAPORE

Carlo Gavazzi Automation
Singapore Pte. Ltd.
61 Tai Seng Avenue #05-06
Print Media Hub @ Paya Lebar
iPark
Singapore 534167
Tel. +65 67 466 990
Fax +65 67 461 980
info@carlogavazzi.com.sg

TAIWAN

Branch of Carlo Gavazzi
Automation Singapore Pte. Ltd.
12F-3, No. 530, Yingcai Rd.,
West Dist., Taichung City
403518,
Taiwan, China
Tel. +886 4 2258 4001
Fax +886 4 2258 4002

MALAYSIA

Carlo Gavazzi Automation (M)
SDN. BHD.
D12-06-G, Block D12,
Pusat Perdagangan Dana 1,
Jalan PJU 1A/46,
47301 - Petaling Jaya,
Selangor, Malaysia
Tel. +60 3 7842 7299
Fax +60 3 7842 7399
info@gavazzi-asia.com

CHINA

Carlo Gavazzi Automation
(China) Co. Ltd.
Unit 2308, 23/F.,
News Building, Block 1,1002
Middle Shennan Zhong Road,
Futian District,
Shenzhen, China
Tel. +86 755 8369 9500
Fax +86 755 8369 9300
info@carlogavazzi.cn

INDIA

Carlo Gavazzi Automation
India PVT LTD.
1105/06, Kamdhenu 23 West,
Thane Belapur Road,
TTC Industrial Area
Kopar Khairane, Navi Mumbai
400709, India
Tel. +91 88282 84033
info@carlogavazzi.in

OUR COMPETENCE CENTRES AND PRODUCTION SITES

DENMARK

Carlo Gavazzi Industri A/S
Hadsten

ITALY

Carlo Gavazzi Controls SpA
Belluno

LITHUANIA

Uab Carlo Gavazzi Industri
Kaunas
Kaunas

MALTA

Carlo Gavazzi Ltd
Zejtun

CHINA

Carlo Gavazzi Automation
(Kunshan) Co., Ltd.
Kunshan

MEXICO

Carlo Gavazzi Americas Inc.
Tijuana

HEADQUARTERS

CARLO GAVAZZI AUTOMATION SPA

Via Milano, 13
I-20045 - Lainate (MI) - ITALY
Tel. +39 02 931 761
info@gavazziautomation.com
www.gavazziautomation.com

Energy to Components!

www.gavazziautomation.com