

Harmony XALD, XALK plastic control stations

For Harmony XB5, control and signaling
units Ø 22



Harmony

Discover [Harmony](#)

Advanced operator interface and industrial relays

Harmony operator interface and industrial relays enhance operational efficiency and equipment availability across industrial and building applications. **Harmony** includes intelligent connected products and edge terminals that visualize, gather and process data, enabling informed operator decisions

Explore our offer

- [Harmony](#) Push Buttons and Switches
- [Harmony](#) HMI Operator Terminals, IPC and EdgeBox
- [Harmony](#) Signaling Devices
- [Harmony](#) Electrical Relays
- [Harmony](#) Safety

Life Is On

Schneider
Electric

General contents

Harmony XALD, XALK plastic control stations

Selection guide	page 2
■ Presentation	page 6
■ References	
□ Complete stations	page 8
□ Stations for customer assembly: empty enclosures	page 13
□ Stations for customer assembly: electrical blocks	page 14
□ Stations for customer assembly: heads	page 15
□ Stations for customer assembly: accessories	page 29
■ Product reference index	page 38

Type of applications	All applications	
Enclosures	Plastic	Glass-reinforced polyester
	Complete stations and separate components for customer assembly	Empty insulated enclosures



Main feature	Pre-drilled control stations		Pre-drilled or undrilled enclosures
Associated control and signaling units	Harmony XB5 with plastic bezel		Harmony XB7, monolithic, plastic Harmony XB4 with metal bezel Harmony XB5 with plastic bezel
Number of cut-outs for Ø 22 control and signaling units	1, 2, 3, 4 or 5	1, 2 or 3 (complete stations) 1, 2, 3, 4 or 5 (empty enclosures)	1, 2 or 3 1, 2, 4, 8 or 16
Material	Polycarbonate		ABS Glass-reinforced polyester
Color	Yellow lid Light gray base	Dark gray lid Light gray base	Light gray or yellow lid Light gray base Coloured gray throughout
Degree of protection	IP66, IP67, IP69, IP69K		IP54 IP65, IP69, IP69K
Function	Emergency Stop or Emergency switching off	Start or Stop Start-Stop with pilot light Motion control	According to equipment fitted: <input type="checkbox"/> Start or Stop <input type="checkbox"/> Start-Stop with pilot light <input type="checkbox"/> Motion control <input type="checkbox"/> Emergency stop
Cable entries	Knock-outs (CM12)		Knock-outs (ISO 20) Undrilled
Type references	XALK	XALD	XALE XAPA

All applications		Specific applications		
Metal	Metal front plate, insulated protective rear cover	Plastic	Metal	
Empty enclosures	Empty, flush mounting enclosures: front plate + rear cover	Control stations for severe environments	Lift inspection stations	Key operated control stations




Pre-drilled enclosures	Pre-drilled or undrilled enclosures	Pre-drilled front plates & rear covers	Pre-drilled empty control stations	Pre-drilled empty enclosures or fitted stations	Fitted stations
Harmony XB4 with metal bezel Harmony XB5 with plastic bezel			Harmony XB5 with plastic bezel	Harmony XB5 or XB7 with plastic bezel	With key lock
8, 16, 24, 30 or 40	1, 2, 3, 4, 5, 6, 8 or 10	1, 2, 3, 4 or 5	1, 2, 3, 4 or 5	1, 2, 3, 4, 5 or 6 with or without power socket	-
Aluminium alloy or sheet steel	Zinc or aluminium alloy	Front plate: brushed aluminium Rear cover: polystyrene	Mineral reinforced polyamide	Polycarbonate	Zinc alloy
Blue lid and base	XAPD, XAPG: Grey lid & base XAPK: Yellow lid & base XAPO: Orange lid & base	Unpainted aluminium	Black lid Black base	Yellow lid Light gray base	Gray
IP54	IP65, IP66, IP69		IP66, IP67, IP69, IP69K	IP44 (with power socket) IP55 or IP66 depending on model	IP54
According to equipment fitted: <input type="checkbox"/> Start or Stop <input type="checkbox"/> Start-Stop with pilot light <input type="checkbox"/> Motion control <input type="checkbox"/> Emergency stop					Start-Stop
<input type="checkbox"/> Tapped entries for cable-glands <input type="checkbox"/> or undrilled	Tapped entries for cable-glands	Knock-outs (with protective rear cover)	Two ISO 20 open entries	<input type="checkbox"/> Knock-outs (CM12) <input type="checkbox"/> or undrilled	Tapped for cable-glands
XB2SL	XAPD, XAPK, XAPG, XAPO	XAPE	XALG	XALF	XAPS

Control stations and enclosures

Plastic control stations XALD and XALK


For Harmony® XB5 control and signaling units Ø 22



Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22



LED rationalization while ensuring the same functionality


Universal LED block for all illuminated functions

Harmony streamline the structure of pilot lights and actuators using LED by moving from 6 colored LEDs to a universal source of luminosity.

A unique technology that leads to the best lighting solution

- > Divide by 6 the stocked part numbers (for a given wiring & voltage solution)
- > Astonishing intensity and contrast with enhanced color purity
- > Reduce conception and installation time
- > Simplified maintenance
- > Avoid errors on pairing between heads and light blocks, nomenclatures are simplified

The universal light blocks are now identifiable in the catalog with the below logo as well as physically on the product with the two letters "UN".



Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Presentation

Harmony® XALD and XALK control stations are available in two forms:

- Complete
- For customer assembly

These control stations use the plastic bezel pushbuttons, switches and pilot lights of the Harmony XB5 range, which offers a wide choice of circular heads.

Complete pre-assembled stations

These are complete, ready to install, stations fitted with 1 to 3 buttons to cater for the most commonly encountered functions:

■ **Start or Stop**, with:

- 1 flush spring return pushbutton,
- 1 red, spring return, mushroom head pushbutton.

■ **Emergency stop or Emergency switching off**, with:

- 1 red, latching, mushroom head pushbutton **3**, either push-pull or turn to release, with or without key.

■ **Start-Stop**, with:

- 2 flush spring return pushbuttons,
- 1 flush spring return pushbutton **1** + 1 projecting spring return pushbutton **2**,
- 1 2-position selector switch **4** + 1 pilot light with Universal LED, if required.

■ **Two functions**, with:

- 2 flush spring return pushbuttons **1**.

■ **Three functions**, with:

- 3 flush spring return pushbuttons **1**,
 - 2 flush spring return pushbuttons **1** + 1 projecting spring return pushbutton **2**,
 - 2 flush spring return pushbuttons **1** + 1 red, latching, mushroom head pushbutton **3**.
- These pushbuttons, switches and pilot lights comprise plastic heads from the Harmony XB5 range and electrical blocks (contact or light) **8** that are mounted in the back of the enclosure.

Stations for customer assemblies

These stations are for assembly by the user and offer a choice of 2 assembly methods:

■ **Box method**

Identical to the pre-assembled versions. The electrical blocks **8** are mounted on a metal mounting plate in the back of the enclosure **7**.

■ **Station method**

The electrical blocks **9** are mounted directly beneath the heads using a body/fixing collar **10**.

It is possible to assemble stations with 1 to 5 heads, each of which can be combined with 3 electrical blocks **8** or **9** (contact or light).

The XAL range offers a wide choice of head types for:

- Spring return pushbuttons **1** or **2**, either marked or unmarked
- Spring return mushroom head pushbuttons
- Latching mushroom head pushbuttons **3**
- Selector switches with standard or long handle and key switches **4**
- Toggle switches
- Pilot lights **5**
- Illuminated spring return pushbuttons **6**
- Illuminated selector switches with standard handle **4**

Accessories for heads

Markings can be customized by using legend holders **11** which can either be fitted with pre-marked legends or legends engraved by the user. Alternatively, paper legends or peel-off legends (supplied on sheet for marking by laser printer) can be used.



Customized products

Presentation (Continued)

Customization

- Markings on pushbutton, illuminated pushbuttons, and pilot lights caps
- Markings on accessories, like legend plates and legend panels
- Color plated bezel pushbuttons
- Marking on control station

Material and colors

- **Start-Stop control stations (XALD):**
light gray base "RAL 7035", dark gray lid "RAL 7016"
- Control stations with **Emergency stop** or **Emergency switching off** functions (**XALK**): light gray "RAL 7035" base, yellow "RAL 7021" lid
- Lid fixing screws and nut material: stainless steel type A4, AISI 316.

Environment

- Protection degree: IP66, IP69 (EN/IEC 60529) and IP69K (ISO20653) and UL/CSA Enclosure type 4, 4X and 13
- Mechanical shock protection level: IK08 (EN50102/IEC60068-2-75)
- High pressure cleaning resistance: 70 x 10⁵ Pa (70 bars), distance 0.1 m (temp. 55° C)
- Ambient air temperature for operation: - 40 to + 70° C
- Conformity to standards :
 - EN/IEC 60947-5-1, 60947-5-4 for **Start-Stop** control stations,
 - EN/IEC 60204-1 and EN/ISO 13850 for control stations with **Emergency stop** function,
 - IEC 60364-5-53 for control stations with **Emergency switching off** function
- Product certifications : UL Listed, CSA, GOST

Connection

- Knock-out entries for cable-gland (CM 12, Pg 13.5 and tapped ISO 20).
- Knock-outs for cable entry through rear.

Control stations and enclosures

Plastic control stations XALD and XALK
 For Harmony XB5 control and signaling units Ø 22
 Complete stations

Start or Stop function

Screw clamp terminal connections (Schneider Electric anti-loosening system)

■ Light gray "RAL 7035" base, dark gray "RAL 7016" lid

Description	Type of push	Dimensions (1) w x h x d mm/in.	Type of contact		Marking	Reference	Weight kg/lb
			NO	NC			
Marking on pushbutton							
1 spring return pushbutton	Flush, green	68 x 68 x 62/ 2.68 x 2.68 x 2.44	1	-	I	XALD102 (2)	0.135/0.298
					Marche	XALD104 (2)	0.156/0.344
					Start	XALD103 (2)	0.156/0.344
1 spring return pushbutton	Flush, red	68 x 68 x 62/ 2.68 x 2.68 x 2.44	1	1	I	XALD102E	0.165/0.364
					O	XALD112	0.156/0.344
					Stop	XALD114 (2)	0.165/0.364
1 spring return pushbutton	Flush, green	68 x 68 x 62/ 2.68 x 2.68 x 2.44	-	1	O	XALD112E	0.165/0.364
					Marche	XALD101 (2)	0.157/0.346
					Start	XALD101H29 (2)	0.157/0.346
1 mushroom head pushbutton, Ø 40 mm/1.57 in., spring return	Red	68 x 68 x 86/ 2.68 x 2.68 x 3.39	-	1	Arrêt	XALD164 (2)	0.182/0.401
					Stop	XALD164H29H7	0.182/0.401

(1) Please see our website www.se.com for more precised information about dimensions of components.

(2) Please add H7 for UL/CSA conformity, example: [XALK102H7](#).



XALD102



XALD101



XALD164

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Complete stations

Emergency stop and Emergency switching off functions conforming to EN/IEC 60204-1, 60364-5-53, EN/ISO 13850, and Machinery Directive 2006/42/EC

Emergency stop function: Mushroom head Emergency stop trigger action and mechanical latching pushbuttons conform to standards EN/IEC 60204-1 and EN/ISO 13850, to Machinery Directive 2006/42/EC and to standard EN/IEC 60947-5-5.

Emergency switching off function: Mushroom head switching off mechanical latching pushbuttons conform to standards IEC 60364-5-53 and EN/IEC 60947-5-5.




Please consult our Customer Care Centre for a full explanation of these standards and directives.

Emergency stop and Emergency switching off functions with trigger action and mechanical latching

Screw clamp terminal connections (Schneider Electric anti-loosening system)

■ Light gray "RAL 7035" base, yellow "RAL 1021" lid

■ Conformity to standards EN/IEC 60204-1, EN/ISO 13850 (1), EN/IEC 60947-5-5 and to Machinery directive 2006/42/CE (2)

Description	Dimensions (3) w x h x d mm/in.	Type of contact			Marking	Reference	Weight kg/lb
		NO	NC	NC MC (6)			
Unmarked							
 XALK178● 1 mushroom head pushbutton, Ø 40 mm/1.57 in., red Turn to release	68 x 68 x 92.5/ 2.68 x 2.68 x 3.64	–	1	–	–	XALK178 (4)	0.194/0.428
		–	2	–	–	XALK178F (4)	0.194/0.428
		–	–	1	–	XALK1786 (4) (6)	0.197/0.434
		1	1	–	–	XALK178E (4)	0.194/0.428
		1	2	–	–	XALK178G (4)	0.194/0.428
 XALK188● 1 mushroom head pushbutton, Ø 40 mm/1.57 in., red Key release (key 455)	68 x 68 x 114.5/ 2.68 x 2.68 x 4.51	–	1	–	–	XALK188 (4)	0.188/0.414
		–	2	–	–	XALK188F	0.188/0.414
		1	1	–	–	XALK188E (4)	0.188/0.414
		1	2	–	–	XALK188G	0.188/0.414
 XALK198● 1 mushroom head pushbutton, Ø 40 mm/1.57 in., red Push-pull	68 x 68 x 91.5/ 2.68 x 2.68 x 3.60	–	1	–	–	XALK198 (4)	0.193/0.425
Marked							
1 mushroom head pushbutton, Ø 40 mm/1.57 in., red Turn to release	68 x 68 x 92.5/ 2.68 x 2.68 x 3.64	–	2	–	EMERGENCY STOP	XALK178FH29	0.194/0.428
		–	2	–	NODSTOPP	XALK178FH49	0.194/0.428
		1	2	–	ARRET D'URGENCE	XALK178GTHFR (5)	0.197/0.434
		1	2	–	NODSTOP	XALK178GTH26 (5)	0.197/0.434
		1	2	–	EMERGENCY STOP	XALK178GTH29 (5)	0.197/0.434
		–	2	–	NODSTOP	XALK188GTH26 (5)	0.188/0.414

(1) Our Customer Care Centre may provide a control station type **XALK1●8** with marking of the Emergency stop function and of the logo in conformity with the requests of EN/ISO 13850 standard, paragraph 4.4.6.

(2) Please consult our Customer Care Centre for full details of these standards and directives.

(3) Please see our website www.se.com for more precised information about dimensions of components.

(4) Please add H7 for UL/CSA conformity, example: **XALK178H7**.

(5) T for direct head mounting on cover with **ZB5AZ009** fixing base.

(6) NC contact block with monitoring dedicated for Emergency stop head only.

Control stations and enclosures

Plastic control stations XALD and XALK
For Harmony XB5 control and signaling units Ø 22
Complete stations

Emergency stop and Emergency switching off functions conforming to EN/IEC 60204-1, 60364-5-53, EN/ISO 13850, and Machinery Directive 2006/42/EC

Emergency stop function: Mushroom head Emergency stop trigger action and mechanical latching pushbuttons conform to standards EN/IEC 60204-1 and EN/ISO 13850, to Machinery Directive 2006/42/EC and to standard EN/IEC 60947-5-5.

Emergency switching off function: Mushroom head switching off mechanical latching pushbuttons conform to standards IEC 60364-5-53 and EN/IEC 60947-5-5.

Please consult our Customer Care Centre for a full explanation of these standards and directives.

Illuminated Emergency stop and Emergency switching off pushbuttons with trigger action and mechanical latching

- Light gray "RAL 7035" base, yellow "RAL 1021" lid
- Conformity to standards EN/IEC 60204-1, EN/ISO 13850 (1), EN/IEC 60947-5-5 and to Machinery directive 2006/42/CE (2)

Description	Type of reset	Signalling type	Type of contact		Supply voltage	Reference	Weight kg/lb
			NO	NC			
Screw clamp terminal connections (Schneider Electric anti-loosening system)							
Complete control station for Ø 22 mm/ 0.866 in. XB5 Emergency stop and Emergency switching off pushbuttons	Turn to release	Fixed white + fixed red, bi-color	1	1	24 V ~	XALK84W3BE	0.182/0.401
			1	2	24 V ~	XALK84W3BG	0.182/0.401
		Fixed, red	1	1	230 V ~	XALK84W2ME	0.182/0.401
			1	2	230 V ~	XALK84W2MG	0.182/0.401
		Fixed white + fixed red, bi-color	1	1	24V ~	XALK178W3B140E	0.180/0.397
			1	2	24V ~	XALK178W3B140G	0.180/0.397
Push-in terminal connections							
Complete control station for Ø 22 mm/ 0.866 in. XB5 Emergency stop and Emergency switching off pushbuttons	Key release (key 4A185)	Fixed, red	1	2	24V ~	XALK188W2B101G5	0.205/0.452




XALK84W3BE



XALK178W3B140E



XALK188W2B101G5

(1) For compliance with EN/ISO 13850 standard, paragraph 4.4.6 Emergency Stop function logo  has been added.

(2) Please consult our Customer Care Centre for full details of these standards and directives.

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Complete stations



XALD224



XALD211H29



XALD134



XALD144



XALD363B

Start-Stop function

Screw clamp terminal connections (Schneider Electric anti-loosening system)

■ Light gray "RAL 7035" base, yellow "RAL 1021" lid

Description	Dimensions (1) w x h x d mm/in.	Type of contact		Marking	Reference	Weight kg/lb
		NO	NC			

Marking on pushbutton (2)

2 spring return pushbuttons: - 1 flush, green - 1 flush, red	68 x 106 x 62/ 2.68 x 4.17 x 2.44	1	–	I O	XALD213 (3)	0.233/0.514
		–	1	Marche Arrêt	XALD224 (3)	0.233/0.514
				Start Stop	XALD215 (3)	0.233/0.514
2 spring return pushbuttons: - 1 flush, green - 1 projecting, red	68 x 106 x 66.5/ 2.68 x 4.17 x 2.62	1	1	I O	XALD213E	0.252/0.556
		1	–	I O	XALD214	0.234/0.516
2 spring return pushbuttons: - 1 flush, green - 1 projecting, red	68 x 106 x 66.5/ 2.68 x 4.17 x 2.62	–	1	Start Stop	XALD225 (3)	0.234/0.516

Marking on legend holder and legend below head

2 spring return pushbuttons: - 1 flush, green - 1 projecting, red	68 x 106 x 62/ 2.68 x 4.17 x 2.44	1	–	Marche Arrêt	XALD211 (3)	0.233/0.514
		–	1	Start Stop	XALD211H29 (3)	0.233/0.514
2 spring return pushbuttons, - 1 flush, green - 1 flush, red	68 x 106 x 62/ 2.68 x 4.17 x 2.44	1	–	Ouverture Fermeture	XALD241	0.233/0.514
		1	–			
1 selector switch with standard handle 2-position stay put	68 x 106 x 80/ 2.68 x 4.17 x 3.15	1	–	O-I	XALD134 (3)	0.163/0.359
		1	–	Arrêt-Marche	XALD132 (3)	0.163/0.359
1 key switch (key 455), key withdrawal from left-hand position	68 x 106 x 105.5/ 2.68 x 4.17 x 4.15	1	–	O-I	XALD144 (3)	0.187/0.412
				Arrêt-Marche	XALD142	0.196/0.432
		1	1	O-I	XALD144E (3)	0.196/0.432

Description	Dimensions (1) w x h x d mm/in.	Type of contact		Marking	Pilot light supply V	Reference	Weight kg/lb
		NO	NC				

With pilot light and marking on pushbutton (2)

2 spring return pushbuttons and 1 red pilot light with Universal LED	68 x 136 x 64.5/ 2.68 x 5.35 x .54	1	–	I O	24 ~	XALD363B	0.261/0.575
		–	1		120 ~	XALD363G (3)	0.261/0.575
					230 ~	XALD363M	0.261/0.575



With pilot light and marking on legend holder and legend below head

2 spring return pushbuttons and 1 red pilot light with Universal LED	68 x 136 x 64.5/ 2.68 x 5.35 x .54	1	–	Marche Arrêt	24 ~	XALD361B	0.261/0.575
		–	1		230 ~	XALD361M (3)	0.261/0.575



(1) Please see our website www.se.com for more precised information about dimensions of components.

(2) Push supplied with cap not clipped-in, allowing orientation through 90° in 360° steps.

(3) Please add H7 for UL/CSA conformity, example: [XALD213H7](#).

Control stations and enclosures

Plastic control stations XALD and XALK
For Harmony XB5 control and signaling units Ø 22
Complete stations



XALD222

Two function

Screw clamp terminal connections (Schneider Electric anti-loosening system)

■ Light gray "RAL 7035" base, yellow "RAL 1021" lid

Description	Dimensions (1) w x h x d mm/in.	Type of contact		Marking	Reference	Weight kg/lb
		NO	NC			
2 spring return pushbuttons: - 1 flush, white - 1 flush, black	68 x 106 x 62/ 2.68 x 4.17 x 2.44	1	–	↑ ↓	XALD222 (4)	0.233/0.514
		1	–	→ ←		
		1	1	↑ ↓	XALD222E	0.233/0.514

Three function

Screw clamp terminal connections (Schneider Electric anti-loosening system)

■ Light gray "RAL 7035" base, yellow "RAL 1021" lid

Description	Dimensions (1) w x h x d mm/in.	Type of contact		Marking	Reference	Weight kg/lb
		NO	NC			
3 spring return pushbuttons: - 1 flush, green - 1 flush, red - 1 flush, green	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	I O	XALD339 (4)	0.298/0.657
		–	1	II		
3 spring return pushbuttons: - 1 flush, white - 1 flush, red - 1 flush, black	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	↑ O ↓	XALD324 (4)	0.298/0.657
		–	1	↓		
3 spring return pushbuttons: - 1 flush, white - 1 projecting, red - 1 flush, black	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	↑ O ↓	XALD326 (4)	0.298/0.657
		–	1	Stop ↓		
3 spring return pushbuttons: - 1 flush, white - 1 projecting, red - 1 flush, black	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	→ O ←	XALD334 (4)	0.298/0.657
		–	1	↓		
3 spring return pushbuttons: - 1 flush, white - 1 projecting, red - 1 flush, black	68 x 136 x 62/ 2.68 x .35 x 2.44	1	1	↑ O ↓	XALD324E	0.317/0.699
		–	1	↓		
3 spring return pushbuttons: - 1 flush, white - 1 projecting, red - 1 flush, black	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	↑ O ↓	XALD325	0.299/0.659
		–	1	↓		
2 spring return + 1 mushroom head pushbuttons: - 1 flush, white - 1 mushroom head, red (3) - 1 flush, black	68 x 136 x 87.5/ 2.68 x .35 x 3.44	1	–	↑ O ↓	XALD328 (4)	0.317/0.699
		–	1	↓		
3 spring return pushbuttons: - 1 flush, green - 1 flush, red - 1 flush, green	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	Avant	XALD311 (4)	0.299/0.659
		–	1	Arrêt		
3 spring return pushbuttons: - 1 flush, green - 1 flush, red - 1 flush, green	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	Arrière	XALD311H29H7	0.299/0.659
		–	1	FORWARD		
3 spring return pushbuttons: - 1 flush, green - 1 flush, red - 1 flush, green	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	STOP	XALD321	0.299/0.659
		–	1	REVERSE		
3 spring return pushbuttons: - 1 flush, green - 1 flush, red - 1 flush, green	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	Montée	XALD321H29H7	0.299/0.659
		–	1	Arrêt		
3 spring return pushbuttons: - 1 flush, green - 1 flush, red - 1 flush, green	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	Descente	XALD321H29H7	0.299/0.659
		–	1	UP		
3 spring return pushbuttons: - 1 flush, green - 1 flush, red - 1 flush, green	68 x 136 x 62/ 2.68 x .35 x 2.44	1	–	STOP	XALD321H29H7	0.299/0.659
		–	1	DOWN		

(1) Please see our website www.se.com for more precised information about dimensions of components.

(2) Push supplied with cap not clipped-in, allowing orientation through 90° in 360° steps.

(3) Standard turn to release, latching, Ø 30 mm/1.181 in.

(4) Please add H7 for UL/CSA conformity, example: XALD22H7.



XALD339



XALD334

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: empty enclosures



XALD02



XALK01H29

Empty control stations with metal mounting plate in the back of enclosure

Description	Text and logo	Dimensions (1) w x h x d mm/in.	Number of cut-outs	Reference	Weight kg/lb
Light gray "RAL 7035" base Dark gray "RAL 7016" lid	Without	68 x 68 x 53/ 2.68 x 2.68 x 2.09	1	XALD01 (6)	0.136/0.300
		68 x 106 x 53/ 2.68 x 4.17 x 2.09	2	XALD02 (6)	0.193/0.425
		68 x 136 x 53/ 2.68 x 5.35 x 2.09	3	XALD03 (6)	0.238/0.525
		68 x 166 x 53/ 2.68 x 6.54 x 2.09	4	XALD04 (6)	0.278/0.613
		68 x 196 x 53/ 2.68 x 7.72 x 2.09	5	XALD05 (6)	0.322/0.710
Light gray "RAL 7035" base Yellow "RAL 1021" lid For Emergency stop function (7)	Without	68 x 68 x 53/ 2.68 x 2.68 x 2.09	1	XALK01 (5) (6)	0.136/0.300
		68 x 106 x 53/ 2.68 x 4.17 x 2.09	2	XALK02	0.193/0.425
		68 x 136 x 53/ 2.68 x 5.35 x 2.09	3	XALK03 (5)	0.238/0.525
		68 x 166 x 53/ 2.68 x 6.54 x 2.09	4	XALK04	0.278/0.613
		68 x 196 x 53/ 2.68 x 7.72 x 2.09	5	XALK05	0.322/0.710
	With text "ARRET D'URGENCE" (2) and logo (3)	68 x 68 x 53/ 2.68 x 2.68 x 2.09	1	XALK01HFR	0.136/0.300
	With text "EMERGENCY STOP" (2) and logo (3)	68 x 68 x 53/ 2.68 x 2.68 x 2.09	1	XALK01H29	0.136/0.300

CSA + UL certified (4)


Light gray "RAL 7035" base Dark gray "RAL 7016" lid	Without	68 x 68 x 53/ 2.68 x 2.68 x 2.09	1	XALD01H7	0.136/0.300
		68 x 106 x 53/ 2.68 x 4.17 x 2.09	2	XALD02H7	0.205/0.425
		68 x 136 x 53/ 2.68 x 5.35 x 2.09	3	XALD03H7	0.238/0.525
		68 x 136 x 53/ 2.68 x 5.35 x 2.09	3	XALD04H7	0.238/0.525
		68 x 136 x 53/ 2.68 x 5.35 x 2.09	3	XALD05H7	0.238/0.525

Empty control stations with direct head mounting on cover with ZB5AZ009 fixing base

Light gray "RAL 7035" base Yellow "RAL 1021" lid For Emergency stop function	With text "NODSTOP" (2) and logo (3)	68 x 68 x 53/ 2.68 x 2.68 x 2.09	1	XALK01TH26	0.136/0.300
--	--	-------------------------------------	---	----------------------------	-------------

(1) Please see our website www.se.com for more precised information about dimensions of components.

(2) For supply of the text in an other language, please consult our Customer Care Centre.

(3) For complying with ISO 13850 standard, paragraph 4.4.6., Emergency Stop function logo  has been added.

(4) Volt-free commoning/earth terminal included.

(5) Please add H7 for UL/CSA conformity, example: [XALD01H7](#).(6) To add customized markings on these references through web customization tool, see [page 7](#).

(7) Red color pushbutton must be used only for Emergency stop function with XALK yellow background.

Control stations and enclosures

Plastic control stations XALD and XALK
For Harmony XB5 control and signaling units Ø 22
Stations for customer assembly: electrical blocks



ZENL1121



ZALV01



ZBE1015



ZBE1025



ZBV01



ZBE302



ZB5AZ009

Electrical blocks and accessories for mounting in back of enclosure

Description	Supply Voltage	Type of contact	Sold in lots of	Unit reference	Weight kg/lb
Electrical blocks with screw clamp terminal connections					
Standard contact blocks (1)	–	NO contact	5	ZENL1111	0.015/0.033
	–	NC contact	5	ZENL1121	0.015/0.033
Universal LED light blocks (1)	24 V ~	–	5	ZALVB1	0.015/0.033
	110...120 V ~	–	5	ZALVG1	0.015/0.033
	230...240 V ~	–	5	ZALVM1	0.015/0.033



Electrical blocks and accessories for mounting on cover with ZB5AZ009 fixing base

Description	Supply Voltage	Type of contact	Sold in lots of	Unit reference	Weight kg/lb
Compact electrical blocks with push-in terminal connections					
Compact contact blocks (1)	–	NO contact	5	ZBE1015	0.007/0.015
	–	NC contact	5	ZBE1025	0.007/0.015

Compact light blocks with push-in terminal connections

Universal LED light blocks (2)	24 V ~	–	5	ZBVB15	0.012/0.026
	110...120 V ~	–	5	ZBVG15	0.012/0.026
	230...240 V ~	–	5	ZBVM15	0.012/0.026



Electrical blocks with screw clamp terminal connections

Standard contact blocks (1)	–	NO contact	5	ZBE101	0.016/0.035
	–	NC contact	5	ZBE102	0.016/0.035
	–	NC contact with monitoring function (3)	5	ZBE302	0.013/0.029
Universal LED light blocks (1)	24 V ~	–	5	ZBVB1	0.016/0.035
	110...120 V ~	–	5	ZBVG1	0.016/0.035
	230...240 V ~	–	5	ZBVM1	0.016/0.035



Description	For use with	Sold in lots of	Unit reference	Weight kg/lb
-------------	--------------	-----------------	----------------	--------------

Electrical blocks with screw clamp terminal connections				
Body/fixing collar	Electrical blocks (contact or light)	10	ZB5AZ009	0.006/0.013

(1) A maximum of 3 electrical blocks can be fitted per associated head, in which only middle position can be for light block.

(2) It is not possible to fit an additional block on the back of these light blocks.

(3) NC contact block with monitoring dedicated for Emergency stop head only.



XB5KS2B4

Annunciators (IP66, IP67, and IP69)				
Characteristics	Supply voltage V	Color	Reference	Weight kg/lb
Continuous or intermittent non-illuminated buzzer 90dB, 6.8kHz	24 ~ - 50 or 60 Hz	–	XB5KSB	0.024/0.053
	110...120 V ~ - 50 or 60 Hz	–	XB5KSG	0.024/0.053
	230...240 ~ - 50 or 60 Hz	–	XB5KSM	0.024/0.053
Continuous or intermittent illuminated buzzer 90dB, 6.8kHz	24 ~ - 50 or 60 Hz	Red	XB5KS2B4	0.024/0.053
	110...120 V ~ - 50 or 60 Hz	Red	XB5KS2G4	0.024/0.053
	230...240 ~ - 50 or 60 Hz	Red	XB5KS2M4	0.024/0.053
	24 ~ - 50 or 60 Hz	Yellow	XB5KS2B8	0.024/0.053
	110...120 V ~ - 50 or 60 Hz	Yellow	XB5KS2G8	0.024/0.053
	230...240 ~ - 50 or 60 Hz	Yellow	XB5KS2M8	0.024/0.053

(1) To add customized markings on these references using web customization tool, see [page 7](#).

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: heads

Heads for spring return pushbuttons - unmarked

Shape of head	Type of push	Color of cap	Reference		Weight kg/lb
			For black bezel	For gray bezel (4)	
	Without cap (1)	–	ZB5AA0	–	0.022/0.049
	Flush, with set of 6 colored caps	6 colors (2)	ZB5AA9	–	0.027/0.060
	Flush	White	ZB5AA1	ZB5AA1C0	0.018/0.040
		Black	ZB5AA2	ZB5AA2C0	0.018/0.040
		Green	ZB5AA3	ZB5AA3C0	0.018/0.040
		Red	ZB5AA4	ZB5AA4C0	0.018/0.040
		Yellow	ZB5AA5	ZB5AA5C0	0.018/0.040
		Blue	ZB5AA6	ZB5AA6C0	0.018/0.040
	Flush with transparent cap, for insertion of legend (3)	White	ZB5AA18	ZB5AA18C0	0.018/0.040
		Green	ZB5AA38	ZB5AA38C0	0.018/0.040
Red		ZB5AA48	ZB5AA48C0	0.018/0.040	
Yellow		ZB5AA58	ZB5AA58C0	0.018/0.040	
Booted (colored silicone) Can be replaced without dismantling the head	White	ZB5AP1S	–	0.014/0.031	
	Black	ZB5AP2S	–	0.014/0.031	
	Green	ZB5AP3S	–	0.014/0.031	
	Red	ZB5AP4S	–	0.014/0.031	
	Yellow	ZB5AP5S	–	0.014/0.031	
	Blue	ZB5AP6S	–	0.014/0.031	
Projecting	White	ZB5AL1	ZB5AL1C0	0.019/0.042	
	Black	ZB5AL2	ZB5AL2C0	0.019/0.042	
	Green	ZB5AL3	ZB5AL3C0	0.019/0.042	
	Red	ZB5AL4	ZB5AL4C0	0.019/0.042	
	Yellow	ZB5AL5	ZB5AL5C0	0.019/0.042	
	Blue	ZB5AL6	ZB5AL6C0	0.019/0.042	
Recessed (high guard)	White	ZB5AA16	ZB5AA16C0	0.019/0.042	
	Black	ZB5AA26	ZB5AA26C0	0.019/0.042	
	Green	ZB5AA36	ZB5AA36C0	0.019/0.042	
	Red	ZB5AA46	ZB5AA46C0	0.019/0.042	
	Yellow	ZB5AA56	ZB5AA56C0	0.019/0.042	
	Blue	ZB5AA66	ZB5AA66C0	0.019/0.042	

(1) Cap to be ordered separately, see page 36.

(2) Head supplied with 6 different colored caps (white, black, green, red, yellow, blue).

(3) For legend ordering information, see page 32.

(4) To add customized markings on these references using the web customization tool, see page 7.

ZB5AA0

ZB5AA5

ZB5AP2S

ZB5AL3

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: heads



ZB5AA331



ZB5AA432



ZB5AL232

Heads for spring return pushbuttons - marked

Shape of head	Type of push	Marking		Color of cap	Reference		Weight kg/lb
		Text	Color		For black bezel	For gray bezel (2)	
	Flush (1)	I	White	Green	ZB5AA331	ZB5AA331C0	0.018/0.040
			Black	White	ZB5AA131	ZB5AA131C0	0.018/0.040
		II	White	Green	ZB5AA336	–	0.018/0.040
		START	White	Green	ZB5AA333	ZB5AA333C0	0.018/0.040
		ON	White	Green	ZB5AA341	–	0.018/0.040
		MARCHE	White	Green	ZB5AA342	–	0.018/0.040
			White	Black	ZB5AA245	–	0.018/0.040
			Black	White	ZB5AA145	–	0.018/0.040
		O	White	Red	ZB5AA432	ZB5AA432C0	0.018/0.040
			Black	Black	ZB5AA232	–	0.018/0.040
		ARRET	White	Red	ZB5AA433	–	0.018/0.040
		STOP	White	Red	ZB5AA434	ZB5AA434C0	0.018/0.040
			Black	Black	ZB5AA234	–	0.018/0.040
		OFF	White	Red	ZB5AA435	–	0.018/0.040
		UP	Black	White	ZB5AA343	–	0.018/0.040
DOWN	White	Black	ZB5AA344	–	0.018/0.040		
	White	Black	ZB5AA335	ZB5AA334C0	0.018/0.040		
†	Black	White	ZB5AA334	ZB5AA335C0	0.018/0.040		
		Projecting (1)	O	White	Red	ZB5AL432	ZB5AL432C0
Black				Black	ZB5AL232	–	0.019/0.042
STOP			White	Red	ZB5AL434	–	0.019/0.042

Mushroom heads for spring return pushbuttons

Shape of head Type of push	Diameter of push mm/in.	Color of push	Reference	Weight kg/lb
	30/1.181	Black	ZB5AC24	0.027/0.060
		Green	ZB5AC34	0.027/0.060
		Red	ZB5AC44	0.027/0.060
		Yellow	ZB5AC54	0.027/0.060
		Blue	ZB5AC64	0.027/0.060
	40/1.575	Black	ZB5AC2	0.046/0.101
		Green	ZB5AC3	0.046/0.101
		Red	ZB5AC4	0.046/0.101
		Yellow	ZB5AC5	0.046/0.101
		Blue	ZB5AC6	0.046/0.101

(1) Push supplied with cap not clipped-in, allowing orientation through 90° in 360° steps.

(2) To add customized markings on these references using the web customization tool, see page 7.



ZB5AC24



ZB5AC2

Control stations and enclosures

Plastic control stations XALD and XALK
 For Harmony XB5 control and signaling units Ø 22
 Stations for customer assembly: heads



ZB5AT2



ZB5AS62



ZB5AS72



ZB5AW733

Mushroom head pushbuttons (1)

Shape of head	Type of reset	Push		Reference	Weight kg/lb
		Diameter Ø mm/in.	Color		
Heads only					
	Push-pull	30/1.181	Black	ZB5AT24	0.044/0.097
		40/1.575	Black	ZB5AT2	0.049/0.108
		60/2.362	Black	ZB5AX2	0.067/0.148
	Turn to release	30/1.181	Black	ZB5AS42	0.040/0.088
		40/1.575	Black	ZB5AS52	0.044/0.097
		40/1.575	Yellow	ZB5AS55	0.044/0.097
		60/2.362	Black	ZB5AS62	0.064/0.141
	Key release (key 455) (2 keys included with head) (2) (3)	30/1.181	Black	ZB5AS72	0.040/0.088
		40/1.575	Black	ZB5AS12	0.044/0.097

Illuminated mushroom head pushbuttons

Shape of head	Type of reset	Push		Reference	Weight kg/lb
		Diameter Ø mm/in.	Color		
	Turn to release	40/1.575	White	ZB5AW713	0.022/0.049
			Green	ZB5AW733	0.022/0.049
			Orange	ZB5AW753	0.022/0.049
			Blue	ZB5AW763	0.022/0.049

(1) These pushbuttons and heads cannot be used for an Emergency stop function. Therefore, it is recommended that a legend with a black or white background is used.

(2) For specific keys, please contact our Customer Care Center.

(3) The symbol indicates key withdrawal position(s).

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Emergency stop and Emergency switching off heads and circular yellow legends

Emergency stop and Emergency switching off functions conforming to EN/IEC 60204-1, 60364-5-53, EN/ISO 13850, and Machinery Directive 2006/42/EC

Emergency stop function: Mushroom head Emergency stop trigger action and mechanical latching pushbuttons conform to standards EN/IEC 60204-1 and EN/ISO 13850, Machinery Directive 2006/42/EC, and standard EN/IEC 60947-5-5.

Emergency switching off function: Mushroom head switching off mechanical latching pushbuttons conform to standards IEC 60364-5-53 and EN/IEC 60947-5-5.

Please contact our Customer Care Center for an explanation of these standards and directives.



ZB5AT84



ZB5AS844



ZB5AS834



ZB5AS934

Emergency stop and switching off pushbuttons with trigger action and mechanical latching (1)

Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of reset	Push		Reference	Weight kg/lb
		Diameter Ø mm/in.	Color		
Heads only					
	Push-pull	30/1.181	Red	ZB5AT844	0.049/0.108
		40/1.575	Red	ZB5AT84	0.049/0.108
		60/2.362	Red	ZB5AX84	0.067/0.148
	Turn to release	30/1.181	Red	ZB5AS834	0.042/0.002
		40/1.575	Red	ZB5AS844	0.046/0.002
	Key release (key 455) (2 keys included with head) (2)(3)	30/1.181	Red	ZB5AS934	0.068/0.003
		40/1.575	Red	ZB5AS944	0.071/0.003
		60/2.362	Red	ZB5AS964	0.092/0.004
	Key release (key 4A185) (2)(3)	40/1.575	Red	ZB5AS944D	0.071/0.003



ZBY9121



ZBY9420



ZBY9W2B330

Circular yellow legends for Emergency stop (4)

Description	Marking	Color	Sold in lots of	Reference	Weight kg/lb
Ø 60 mm/2.362 in. legend for Emergency stop function	–	Yellow	5	ZBY9121	0.007/0.015
	EMERGENCY STOP	Yellow	5	ZBY9320	0.007/0.015
	ARRET D'URGENCE	Yellow	5	ZBY9120	0.007/0.015
	NOT HALT	Yellow	5	ZBY9220	0.007/0.015
	PARADA DE EMERGENCIA	Yellow	5	ZBY9420	0.007/0.015
	ARRESTO DI EMERGENZA	Yellow	5	ZBY9620	0.007/0.015

Illuminated rings for Emergency stop (4) (5)

Description	Marking	Marking Signaling	Color	Sold in lots of	Reference	Weight kg/lb
Ø 60 mm/2.362 in. illuminated ring for Emergency stop	EMERGENCY STOP	Fixed, red 24 V ~	Yellow	1	ZBY9W2B330	0.031/0.068
	ARRET D'URGENCE	Fixed, red 24 V ~	Yellow	1	ZBY9W2B130	0.031/0.068
	NOT HALT	Fixed, red 24 V ~	Yellow	1	ZBY9W2B230	0.031/0.068

(1) It is recommended that a legend or yellow background is used.

(2) The symbol indicates key withdrawal position(s).

(3) For specific keys, please contact our Customer Care Center.

(4) For compliance with standard EN/ISO 13850, paragraph 4.4.6, the Emergency Stop function logo has been added.

(5) For additional references, see page 33.


Control stations and enclosures

Plastic control stations XALD and XALK
 For Harmony XB5 control and signaling units Ø 22
 Emergency stop and Emergency switching off heads and circular yellow legends

Emergency stop and Emergency switching off functions conforming to EN/IEC 60204-1, 60364-5-53, EN/ISO 13850, and Machinery Directive 2006/42/EC

Emergency stop function: Mushroom head Emergency stop trigger action and mechanical latching pushbuttons conform to standards EN/IEC 60204-1 and EN/ISO 13850, Machinery Directive 2006/42/EC, and standard EN/IEC 60947-5-5. Emergency switching off function: Mushroom head switching off mechanical latching pushbuttons conform to standards IEC 60364-5-53 and EN/IEC 60947-5-5. Please contact our Customer Care Center for an explanation of these standards and directives.

Illuminated and non illuminated Emergency stop and Emergency switching off pushbuttons with trigger action and mechanical latching

Shape of head	Type of reset	Signaling type	Type of contact	Supply voltage V	Diameter Ø mm/in.	Color of the push	Reference	Weight kg/lb
Heads only								
	Turn to release	–		–	60/2.362	Red	ZB5AS84W00	0.055/0.121
		Fixed, red		24 ~	60/2.362	Red	ZB5AS84W2B	0.055/0.121
		Fixed, red		120 ~	60/2.362	Red	ZB5AS84W2G	0.055/0.121
		Fixed, red		230 ~	60/2.362	Red	ZB5AS84W2M	0.055/0.121
		Fixed white + fixed red, bi-color		24 ~	60/2.362	Red	ZB5AS84W3B	0.055/0.121




ZB5AS84W2B

Empty control stations with metal mounting plate in the back of enclosure (1)

Description	Dimensions (4) w x h x d mm/in.	Number of cut-outs	Reference	Weight kg/lb
Light gray "RAL 7035" base Yellow "RAL 1021" lid For Emergency stop function (2)(3)	68 x 68 x 53/ 2.68 x 2.68 x 2.09	1	XALKW01	0.116/0.56



XALKW01

(1) For compliance with standard EN/ISO 13850, paragraph 4.4.6, the Emergency Stop function logo  has been added.
 (2) Compatible only with illuminated Emergency stop pushbuttons ZB5AS84W●● and illuminated rings ZBY9W●●.
 (3) Red color pushbutton must be used only for Emergency stop function with XALK yellow background.
 (4) Please see our website www.se.com for more precised information about dimensions of components.

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Emergency stop and Emergency switching off heads and circular yellow legends


Emergency stop and Emergency switching off functions conforming to EN/IEC 60204-1, 60364-5-53, EN/ISO 13850, and Machinery Directive 2006/42/EC

Emergency stop function: Mushroom head Emergency stop trigger action and mechanical latching pushbuttons conform to standards EN/IEC 60204-1 and EN/ISO 13850, Machinery Directive 2006/42/EC, and standard EN/IEC 60947-5-5. Emergency switching off function: Mushroom head switching off mechanical latching pushbuttons conform to standards IEC 60364-5-53 and EN/IEC 60947-5-5.

Please contact our Customer Care Center for an explanation of these standards and directives.

Illuminated Emergency stop and Emergency switching off functions, mechanical latching pushbuttons with mechanical state indicator

For elevator inspection box applications

Shape of head	Type of reset	Push Diameter Ø mm/in.	Color	Unit reference	Weight kg/lb
Heads only (1)					
	Push-pull (2) For Emergency stop and Emergency switching off function	40/1.575	Red	ZB5AT8643M	0.034/0.075



ZB5AT8643M




ZB5AT8643M330

Description	Conforming to standards	Marking on yellow background	Sold in lots of	Reference	Weight kg/lb
Illuminated Emergency stop function ZB5AT8643M with Ø 60mm / 2.362 in. legend plate	EN/IEC 60204-1 and EN/ISO 13850	–	10	ZB5AT8643M140	0.034/0.075
		ARRET D'URGENCE	10	ZB5AT8643M130	0.034/0.075
		EMERGENCY STOP	10	ZB5AT8643M330	0.034/0.075
		NOT HALT	10	ZB5AT8643M230	0.034/0.075
		PARADA DE EMERGENCIA	10	ZB5AT8643M430	0.034/0.075
		ARRESTO DI EMERGENZA	10	ZB5AT8643M630	0.034/0.075

Illuminated Emergency switching off function only, mechanical latching pushbuttons

Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of reset	Push Diameter Ø mm/in.	Color	Reference	Weight kg/lb
	Turn to release	40/1.575	Red	ZB5AW743	0.022/0.049



ZB5AW743

Circular yellow legends for ZB5AW743

Diameter mm/in.	Conforming to standards	Marking on yellow background	Sold in lots of	Reference	Weight kg/lb
Used for "Emergency switching off" function					
60/2.362	EN/IEC 60204-1	–	10	ZBY9101	0.004/0.009
		COUPURE D'URGENCE	10	ZBY9160	0.004/0.009
		EMERGENCY SWITCHING OFF	10	ZBY9360	0.004/0.009
		NOT-AUS	10	ZBY9260	0.004/0.009



ZBY9360

(1) Only for use with bodies comprising a light source with universal LED.

(2) Cannot be used with metal guards [ZBZ160](#).

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22


General safe stops

General safe stops

General safe stops are used to stop the operation of a machine in a safe manner. These devices cannot be used as an Emergency stop and must not be associated with a yellow background. General safe stops comprise a yellow bezel and black head.



ZB5AS842Y

Shape of head	Type of reset	Push		Reference	Weight kg/lb
		Diameter Ø mm/in.	Color		
	Turn to release	40/1.575	Black	ZB5AS842Y	0.046/0.101

Bellows for harsh environments (1)



ZBZ58

Description	Material	For use with	Color	Sold in lots of	Unit reference	Weight kg/lb
For use in environments subject to humidity, dust, high pressure cleaning, etc.	Silicone	Other functions	Black	2	ZBZ28	0.009/0.020
		Emergency stop/switching off function	Yellow	2	ZBZ58	0.009/0.020

(1) Not compatible with Ø 30 mm/1.181 in. pushbuttons.






















Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: heads

Heads for selector switches (1)

Shape of head	Type of operator	Number and type of positions	Reference		Weight kg/lb	
			For black bezel	For gray bezel (2)		
		2 - stay put		ZB5AD2	ZB5AD2C0	0.017/0.037
		2 - spring return from right to left		ZB5AD4	ZB5AD4C0	0.020/0.044
		3 - stay put		ZB5AD3	ZB5AD3C0	0.017/0.037
		3 - spring return to centre		ZB5AD5	ZB5AD5C0	0.017/0.037
		3 - spring return from left to centre		ZB5AD7	ZB5AD7C0	0.017/0.037
		3 - spring return from right to centre		ZB5AD8	ZB5AD8C0	0.017/0.037
	Standard handle, white	2 - stay put		ZB5AD201	ZB5AD201C0	0.017/0.037
		2 - spring return from right to left		-	ZB5AD401C0	0.020/0.044
		3 - stay put		ZB5AD301	ZB5AD301C0	0.017/0.037
		3 - spring return to centre		ZB5AD501	ZB5AD501C0	0.017/0.037
		3 - spring return from left to centre		-	ZB5AD701C0	0.017/0.037
		3 - spring return from right to centre		-	ZB5AD801C0	0.017/0.037
Standard handle, green	Standard handle, green	2 - stay put		ZB5AD203	ZB5AD203C0	0.017/0.037
		2 - spring return from right to left		-	ZB5AD403C0	0.020/0.044
		3 - stay put		ZB5AD303	ZB5AD303C0	0.017/0.037
		3 - spring return to centre		ZB5AD503	ZB5AD503C0	0.017/0.037
		3 - spring return from left to centre		-	ZB5AD703C0	0.017/0.037
		3 - spring return from right to centre		-	ZB5AD803C0	0.017/0.037

(1) Can only be used for actuation of end of row (side) mounted contacts.



























(2) To add customized markings on these references using the web customization tool, see page 7.

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: heads

Heads for selector switches (1) (continued)						
Shape of head	Type of operator	Number and type of positions	Reference		Weight kg/lb	
			For black bezel	For gray bezel (2)		
	Standard handle, red	2 - stay put		ZB5AD204	ZB5AD204C0	0.017/0.037
		2 - spring return from right to left		-	ZB5AD404C0	0.020/0.044
		3 - stay put		ZB5AD304	ZB5AD304C0	0.017/0.037
		3 - spring return to centre		-	ZB5AD504C0	0.017/0.037
		3 - spring return from left to centre		-	ZB5AD704C0	0.017/0.037
		3 - spring return from right to centre		-	ZB5AD804C0	0.017/0.037
	Standard handle, yellow	2 - stay put		ZB5AD205	ZB5AD205C0	0.017/0.037
		2 - spring return from right to left		-	ZB5AD405C0	0.020/0.044
		3 - stay put		ZB5AD305	ZB5AD305	0.017/0.037
		3 - spring return to centre		-	ZB5AD505	0.017/0.037
		3 - spring return from left to centre		-	ZB5AD705	0.017/0.037
		3 - spring return from right to centre		-	ZB5AD805	0.017/0.037
	Standard handle, blue	2 - stay put		ZB5AD206	ZB5AD206	0.017/0.037
		2 - spring return from right to left		-	ZB5AD406	0.020/0.044
		3 - stay put		ZB5AD306	ZB5AD306	0.017/0.037
		3 - spring return to centre		ZB5AD506	ZB5AD506	0.017/0.037
		3 - spring return from left to centre		-	ZB5AD706	0.017/0.037
		3 - spring return from right to centre		ZB5AD806	ZB5AD806	0.017/0.037
	Long handle, black	2 - stay put		ZB5AJ2	ZB5AJ2C0	0.017/0.037
		2 - spring return from right to left		ZB5AJ4	ZB5AJ4C0	0.020/0.044
		3 - stay put		ZB5AJ3	ZB5AJ3C0	0.017/0.037
		3 - spring return to centre		ZB5AJ5	ZB5AJ5C0	0.017/0.037
		3 - spring return from left to centre		ZB5AJ7	ZB5AJ7C0	0.017/0.037
		3 - spring return from right to centre		ZB5AJ8	ZB5AJ8C0	0.017/0.037

(1) Can only be used for actuation of end of row (side) mounted contacts.

(2) To add customized markings on these references using the web customization tool, see page 7.

Control stations and enclosures























Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: heads



ZB5AD39

Heads for selector switches (1) (continued)						
Shape of head	Type of operator	Number and type of positions (2)		Reference		Weight kg/lb
				For black bezel	For gray bezel (4)	
	Knurled knob, black (3)	2 - stay put		ZB5AD29	ZB5AD29C0	0.020/0.044
		2 - spring return from right to left		–	ZB5AD49C0	0.024/0.053
		3 - stay put		ZB5AD39	ZB5AD39C0	0.020/0.044
		3 - spring return to centre		ZB5AD59	ZB5AD59C0	0.020/0.044
		3 - spring return from left to centre		–	ZB5AD79C0	0.020/0.044
		3 - spring return from right to centre		–	ZB5AD89C0	0.020/0.044
	Key switch with key 455 (3)	2 - stay put		ZB5AG2	ZB5AG2C0	0.057/0.126
				ZB5AG02	–	0.057/0.126
				ZB5AG4	ZB5AG4C0	0.057/0.126
		2 - spring return from right to left		ZB5AG6	ZB5AG6C0	0.061/0.134
		3 - stay put		ZB5AG0	ZB5AG0C0	0.057/0.126
				ZB5AG3	ZB5AG3C0	0.057/0.126
				ZB5AG5	–	0.057/0.126
				ZB5AG9	ZB5AG9C0	0.057/0.126
				ZB5AG09	–	0.057/0.126
		3 - spring return from left to centre		ZB5AG1	–	0.057/0.126
		3 - spring return to centre		ZB5AG7	ZB5AG7C0	0.057/0.126
		3 - spring return from right to centre		ZB5AG8	–	0.057/0.126
		ZB5AG05	ZB5AG05C0	0.057/0.126		
		ZB5AG08	ZB5AG08C0	0.057/0.126		

(1) Can only be used for actuation of end of row (side) mounted contacts.

(2) The symbol "U" indicates key withdrawal position(s).

(3) For specific keys, please contact our Customer Care Center.

(4) To add customized markings on these references using the web customization tool, see [page 7](#).

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: heads



ZB5AG2DC0



ZB5AG●●



ZB5AD28



ZB5AD2804C0

Heads for selector switches (1) (continued)						
Shape of head	Type of operator	Number and type of positions (2)		Reference		Weight kg/lb
				For black bezel	For gray bezel (3)	
	Key switch with key 8D1	2 - stay put		ZB5AG2D	ZB5AG2DC0	0.057/0.126
				ZB5AG02D	-	0.057/0.126
				ZB5AG4D	ZB5AG4DC0	0.057/0.126
		2 - spring return from right to left		ZB5AG6D	-	0.061/0.134
			3 - stay put		ZB5AG0D	-
				ZB5AG3D	-	0.057/0.126
				ZB5AG03D	-	0.057/0.126
		3 - spring return from left to centre to centre		ZB5AG07D	-	0.057/0.126
		3 - spring return to centre		ZB5AG7D	-	0.057/0.126

Heads for toggle switches									
Shape of head	Description	Lever	Type of position	Reference		Weight kg/lb			
				For black bezel	For gray bezel (3)				
	2-position	Black	Stay put		ZB5AD28	ZB5AD28C0	0.023/0.051		
					-	ZB5AD48C0	0.023/0.051		
			White	Stay put		ZB5AD2801	ZB5AD2801C0	0.023/0.051	
						ZB5AD2804	ZB5AD2804C0	0.023/0.051	
				Blue	Stay put		-	ZB5AD2806C0	0.023/0.051

(1) Can only be used for actuation of end of row (side) mounted contacts.

(2) The symbol "Ω" indicates key withdrawal position(s).

(3) To add customized markings on these references using the web customization tool, see page 7.

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: heads



ZB5AV053

Heads for pilot lights					
Shape of head	For use with body comprising light source type	Color of lens	Reference	Weight kg/lb	
With plain lens					
	With Universal LED 	White	ZB5AV013	0.017/0.037	
		Green	ZB5AV033	0.017/0.037	
		Red	ZB5AV043	0.017/0.037	
		Orange	ZB5AV053	0.017/0.037	
		Yellow	ZB5AV083	0.017/0.037	
		Blue	ZB5AV063	0.017/0.037	
With plain lens, for insertion of legend (1)					
	With Universal LED 	White	ZB5AV013E	0.017/0.037	
		Green	ZB5AV033E	0.017/0.037	
		Red	ZB5AV043E	0.017/0.037	
		Orange	ZB5AV053E	0.017/0.037	
		Yellow	ZB5AV083E	0.017/0.037	
		Blue	ZB5AV063E	0.017/0.037	
With grooved lens (2)					
	With Universal LED 	White	ZB5AV013S	0.017/0.037	
		Green	ZB5AV033S	0.017/0.037	
		Red	ZB5AV043S	0.017/0.037	
		Orange	ZB5AV053S	0.017/0.037	
		Yellow	ZB5AV083S	0.017/0.037	
		Blue	ZB5AV063S	0.017/0.037	



ZB5AW313



ZB5AW363



ZB5AW383C0



ZB5AW143

Heads for spring return illuminated pushbuttons					
Shape of head	Type of push	Color	Reference		Weight kg/lb
			For black bezel	For gray bezel (3)	
Only for use with bodies comprising a light source with Universal LED					
	Flush, plain lens 	White	ZB5AW313	ZB5AW313C0	0.017/0.037
		Green	ZB5AW333	ZB5AW333C0	0.017/0.037
		Red	ZB5AW343	ZB5AW343C0	0.017/0.037
		Orange	ZB5AW353	ZB5AW353C0	0.017/0.037
		Yellow	ZB5AW383	ZB5AW383C0	0.017/0.037
		Blue	ZB5AW363	ZB5AW363C0	0.017/0.037
	Flush, grooved lens (2) 	White	ZB5AW313S	ZB5AW313SC0	0.016/0.035
		Green	ZB5AW333S	ZB5AW333SC0	0.016/0.035
		Red	ZB5AW343S	ZB5AW343SC0	0.016/0.035
		Orange	ZB5AW353S	ZB5AW353SC0	0.016/0.035
		Yellow	ZB5AW383S	ZB5AW383SC0	0.016/0.035
		Blue	ZB5AW363S	ZB5AW363SC0	0.016/0.035
	Flush for insertion of legend (1) 	White	ZB5AA18	ZB5AA18C0	0.018/0.040
		Green	ZB5AA38	ZB5AA38C0	0.018/0.040
		Red	ZB5AA48	ZB5AA48C0	0.018/0.040
		Orange	ZB5AA58	ZB5AA58C0	0.018/0.040
		Yellow	ZB5AA88	ZB5AA88C0	0.018/0.040
		Blue	ZB5AA68	ZB5AA68C0	0.018/0.040
	Projecting 	White	ZB5AW113	ZB5AW113C0	0.018/0.040
		Green	ZB5AW133	ZB5AW133C0	0.018/0.040
		Red	ZB5AW143	ZB5AW143C0	0.018/0.040
		Orange	ZB5AW153	ZB5AW153C0	0.018/0.040
		Yellow	ZB5AW183	ZB5AW153C0	0.018/0.040
		Blue	ZB5AW163	ZB5AW163C0	0.018/0.040

Other versions Heads for flush pushbuttons with illuminated ring. Please consult our Customer Care Centre.

(1) For legend ordering information: see page 32.

(2) For use in bright ambient light conditions (for example, outdoors in sunlight).

(3) To add customized markings on these references using the web customization tool, see page 7.



Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: heads

Heads for illuminated selector switches with standard handle

Shape of head	Number and type of positions	Color of handle	Reference		Weight kg/lb	
			For black bezel	For gray bezel (1)		
  Universal for all color heads						
	2 - stay put		White	ZB5AK1213	ZB5AK1213C0	0.016/0.035
			Green	ZB5AK1233	ZB5AK1233C0	0.016/0.035
			Red	ZB5AK1243	ZB5AK1243C0	0.016/0.035
			Orange	ZB5AK1253	ZB5AK1253C0	0.016/0.035
			Yellow	ZB5AK1283	ZB5AK1283C0	0.016/0.035
			Blue	ZB5AK1263	ZB5AK1263C0	0.016/0.035
	2 - spring return from right to left		White	ZB5AK1413	ZB5AK1413C0	0.017/0.037
			Green	ZB5AK1433	ZB5AK1433C0	0.017/0.037
			Red	ZB5AK1443	ZB5AK1443C0	0.017/0.037
			Orange	ZB5AK1453	ZB5AK1453C0	0.017/0.037
			Yellow	ZB5AK1483	ZB5AK1483C0	0.017/0.037
			Blue	ZB5AK1463	ZB5AK1463C0	0.017/0.037
	3 - stay put		White	ZB5AK1313	ZB5AK1313C0	0.016/0.035
			Green	ZB5AK1333	ZB5AK1333C0	0.016/0.035
			Red	ZB5AK1343	ZB5AK1343C0	0.016/0.035
			Orange	ZB5AK1353	ZB5AK1353C0	0.016/0.035
			Yellow	ZB5AK1383	ZB5AK1383C0	0.016/0.035
			Blue	ZB5AK1363	ZB5AK1363C0	0.016/0.035
	3 - spring return to centre		White	ZB5AK1513	ZB5AK1513C0	0.016/0.035
			Green	ZB5AK1533	ZB5AK1533C0	0.016/0.035
			Red	ZB5AK1543	ZB5AK1543C0	0.016/0.035
			Orange	ZB5AK1553	ZB5AK1553C0	0.016/0.035
			Yellow	ZB5AK1583	ZB5AK1583C0	0.016/0.035
			Blue	ZB5AK1563	ZB5AK1563C0	0.016/0.035
	3 - spring return from right to centre		White	ZB5AK1813	ZB5AK1813C0	0.016/0.035
			Green	ZB5AK1833	ZB5AK1833C0	0.016/0.035
			Red	ZB5AK1843	ZB5AK1843C0	0.016/0.035
			Orange	ZB5AK1853	ZB5AK1853C0	0.016/0.035
			Yellow	ZB5AK1883	ZB5AK1883C0	0.016/0.035
			Blue	ZB5AK1863	ZB5AK1863C0	0.016/0.035
	3 - spring return from left to centre		White	ZB5AK1713	ZB5AK1713C0	0.016/0.035
			Green	ZB5AK1733	ZB5AK1733C0	0.016/0.035
			Red	ZB5AK1743	ZB5AK1743C0	0.016/0.035
			Orange	ZB5AK1753	ZB5AK1753C0	0.016/0.035
			Yellow	ZB5AK1783	ZB5AK1783C0	0.016/0.035
			Blue	ZB5AK1763	ZB5AK1763C0	0.016/0.035

(1) To add customized markings on these references using the web customization tool, see [page 7](#).

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: accessories



ZBZ34



ZBY4H101

30 x 40 mm legend holders (flush mounting with bezel) for 8 x 27 mm legends (1)

Description	Legend Background color	Sold in lots of	Unit reference	Weight kg/lb
Without legend	–	10	ZBZ34	– 0.003/0.007
With blank legend	Black or red	10	ZBY2H101	– 0.004/0.009
	White or yellow	10	ZBY4H101	– 0.004/0.009
With blank legend for square heads		10	ZBCZ34	– 0.002/0.004

Standard 30 x 40 mm legend holders for 8 x 27 mm legends (1)

Description	Legend		Sold in lots of	Unit reference		Weight kg/lb
	Color	Marking		For black bezel	For gray bezel (4)	
Without legend	–	–	10	ZBZ32	ZBZ32C0	0.001/0.002
With blank legend (for engraving)	Black or red	–	10	ZBY2101	ZBY2101C0	0.002/0.004
	White or yellow	–	10	ZBY4101	ZBY4101C0	0.002/0.004
With 8 x 27 mm/ 0.315 x 1.063 in. legend (with international marking)	Black or red (2)	I	10	ZBY2147	–	0.002/0.004
		O-I	10	ZBY2178	ZBY2178C0	0.002/0.004
		I-II	10	ZBY2179	–	0.002/0.004
		I-O-II	10	ZBY2186	ZBY2186C0	0.002/0.004
		STOP	10	ZBY2304	ZBY2304C0	0.002/0.004
With 8 x 27 mm/ 0.315 x 1.063 in. legend (with French language marking)	Black or red (2)	ARRET (red background)	10	ZBY2104	ZBY2104C0	0.002/0.004
		ARRET-MARCHE	10	ZBY2166	ZBY2166C0	0.002/0.004
		AUTO-MAIN	10	ZBY2164	–	0.002/0.004
		AUTO-O-MAIN	10	ZBY2185	–	0.002/0.004
		DEFAUT (Black background)	10	ZBY2134	–	0.002/0.004
		DEFAUT (Red background)	10	ZBY2135	–	0.002/0.004
		DEPART CYCLE	10	ZBY2195	–	0.002/0.004
		DESCENTE	10	ZBY2108	–	0.002/0.004
		EN SERVICE	10	ZBY2111	–	0.002/0.004
		FERMETURE	10	ZBY2114	–	0.002/0.004
		MARCHE	10	ZBY2103	ZBY2103C0	0.002/0.004
		MONTEE	10	ZBY2107	–	0.002/0.004
		OUVERTURE	10	ZBY2113	–	0.002/0.004
REARMEMENT (red background)	10	ZBY2123	–	0.002/0.004		
REARMEMENT (black background)	10	ZBY0123	–	0.002/0.004		
SOUS TENSION	10	ZBY2126	–	0.002/0.004		
Red	ARRET D'URGENCE	10	ZBY2130 (3)	–	0.002/0.004	



ZBZ32



ZBY2101




ZBY2104C0



ZBY2107

(1) For legends, see page 31.

(2) "Start" functions: white letters on black background. "Stop" functions: white letters on red background (unless otherwise specified above).

(3) For compliance with standard EN/ISO 13850, paragraph 4.4.6, the Emergency Stop function logo  has been added.

(4) To add customized markings on these references using the web customization tool, see page 7.



Control stations and enclosures

Plastic control stations XALD and XALK


For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: accessories

Standard 30 x 40 mm legend holders with 8 x 27 mm legends (continued)

Description	Legend		Sold in lots of	Reference		Weight kg/lb	
	Color	Marking		For black bezel	For gray bezel (3)		
 ZBY2303	With legend (with English language marking)	Black or red background (1)	AUTO-HAND	10	ZBY2364	–	0.002/0.004
			AUTO-O-HAND	10	ZBY2385	–	0.002/0.004
			CLOSE	10	ZBY2314	–	0.002/0.004
			FORWARD	10	ZBY2305	–	0.002/0.004
			OFF	10	ZBY2312	–	0.002/0.004
			OFF-ON	10	ZBY2367	ZBY2367C0	0.002/0.004
			ON	10	ZBY2311	–	0.002/0.004
			OPEN	10	ZBY2313	–	0.002/0.004
			POWER ON	10	ZBY2326	–	0.002/0.004
			RESET (red background)	10	ZBY2323	–	0.002/0.004
			RESET (black background)	10	ZBY2322	–	0.002/0.004
			REVERSE	10	ZBY2306	–	0.002/0.004
			RUN	10	ZBY2334	–	0.002/0.004
			START	10	ZBY2303	ZBY2303C0	0.002/0.004
			STOP-START	10	ZBY2366	–	0.002/0.004
				Red background	EMERGENCY STOP	10	ZBY2330 (2)
 ZBY2364	With legend (with German language marking)	Black or red background (1)	AUTO-HAND	10	ZBY2364	–	0.002/0.004
			AUTO-O-HAND	10	ZBY2385	–	0.002/0.004

(1) "Start" functions: white letters on black background. "Stop" functions: white letters on red background (unless otherwise specified above).

(2) For compliance with standard EN/ISO 13850, paragraph 4.4.6, the Emergency Stop function logo  has been added.

(3) To add customized markings on these references using the web customization tool, see [page 7](#).

Control stations and enclosures

Plastic control stations XALD and XALK


For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: accessories

Legends (8 x 27 mm) for engraving				
For use with	Color of background	Sold in lots of	Unit reference	Weight kg/lb
30 x 40 mm/1.181 x 1.575 in. legend holder	Black or red	10	ZBY0101	0.001/0.002
	White or yellow	10	ZBY0102	0.001/0.002

Sheets of 76 (8 x 27 mm) peel-off legends				
For use with	Supplied with	Sold in lots of	Unit reference	Weight kg/lb
30 x 40 mm/1.181 x 1.575 in. legend holders ZBZ32 and ZBZ34	Backing board and protective transparent cover	10	ZBY4100	0.043/0.095

8 x 27 mm marked legends (for 30 x 40 mm legend holders ZBZ32 and ZBZ34)				
Language	Color of background	Marking	Reference	Weight kg/lb
International	Black or red (2)	O-I	ZBY02178	0.001/0.002
		STOP	ZBY02304	0.001/0.002
French	Black or red (2)	AUTO-O-MAIN	ZBY02185	0.001/0.002
		MARCHE	ZBY02103	0.001/0.002
		SOUS TENSION	ZBY02126	0.001/0.002

(1) For compliance with standard EN/ISO 13850, paragraph 4.4.6, the Emergency Stop function  has been added.


(2) "Start" functions: white characters on black background. "Stop" functions: white characters on red background (unless otherwise stated above).



ZBY02178

Control stations and enclosures

Plastic control stations XALD and XALK
For Harmony XB5 control and signaling units Ø 22
Stations for customer assembly: accessories



ZBY1●●●

Legends for pushbuttons, switches and pilot lights XB5A

Description	Marking	Text	Sold in lots of	Unit reference	Weight kg/lb
Sheets of 66 circular peel-off transparent self-adhesive legends	Without		10	ZBY1101	0.017/0.037
	International	I	10	ZBY1147	0.017/0.037

Circular yellow legends for mushroom head pushbuttons

Used for "Emergency stop" function (1)


Diameter mm/in.	Conforming to standards	Marking on yellow background	Unit reference	Weight kg/lb
60/2.362	EN/IEC 60204-1 and EN/ISO 13850	–	ZBY9121	0.004/0.009
		ARRET D'URGENCE	ZBY9120	0.004/0.009
		EMERGENCY STOP	ZBY9320	0.004/0.009
		NOT-HALT	ZBY9220	0.004/0.009
		PARADA DI EMERGENCIA	ZBY9420	0.004/0.009
		ARRESTO DE EMERGENZA	ZBY9620	0.004/0.009



ZBY9160

Used for "Emergency switching off" function

60/2.362	EN/IEC 60204-1	–	ZBY9101	0.004/0.009
		COUPURE D'URGENCE	ZBY9160	0.004/0.009
		EMERGENCY SWITCHING OFF	ZBY9360	0.004/0.009
		NOT-AUS	ZBY9260	0.004/0.009

(1) For compliance with standard EN/ISO 13850, paragraph 4.4.6, the Emergency Stop function logo  has been added.

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: accessories

Illuminated rings for Emergency stop (1)(2)


Description	Marking	Signaling	Supply voltage	Color	Sold in lots of	Reference	Weight kg/lb
Ø 60 mm/2.362 in. illuminated ring for Emergency stop	EMERGENCY STOP	Fixed, red	24 V ~	Yellow	1	ZBY9W2B330	0.031/0.068
	ARRET D'URGENCE	Fixed, red	24 V ~	Yellow	1	ZBY9W2B130	0.031/0.068
	NOT HALT	Fixed, red	24 V ~	Yellow	1	ZBY9W2B230	0.031/0.068
	PARADA DE EMERGENCIA	Fixed, red	24 V ~	Yellow	1	ZBY9W2B430	0.031/0.068
	ARRESTO DI EMERGENZA	Fixed, red	24 V ~	Yellow	1	ZBY9W2B630	0.031/0.068
	–	Fixed, red	24 V ~	Yellow	1	ZBY9W2B140	0.031/0.068
	EMERGENCY STOP	Fixed, red	120 V ~	Yellow	1	ZBY9W2G330	0.031/0.068
	ARRET D'URGENCE	Fixed, red	120 V ~	Yellow	1	ZBY9W2G130	0.031/0.068
	NOT HALT	Fixed, red	120 V ~	Yellow	1	ZBY9W2G230	0.031/0.068
	PARADA DE EMERGENCIA	Fixed, red	120 V ~	Yellow	1	ZBY9W2G430	0.031/0.068
	ARRESTO DI EMERGENZA	Fixed, red	120 V ~	Yellow	1	ZBY9W2G630	0.031/0.068
	–	Fixed, red	120 V ~	Yellow	1	ZBY9W2G140	0.031/0.068
	EMERGENCY STOP	Fixed, red	230 V ~	Yellow	1	ZBY9W2M330	0.031/0.068
	ARRET D'URGENCE	Fixed, red	230 V ~	Yellow	1	ZBY9W2M130	0.031/0.068
	NOT HALT	Fixed, red	230 V ~	Yellow	1	ZBY9W2M230	0.031/0.068
	PARADA DE EMERGENCIA	Fixed, red	230 V ~	Yellow	1	ZBY9W2M430	0.031/0.068
	ARRESTO DI EMERGENZA	Fixed, red	230 V ~	Yellow	1	ZBY9W2M630	0.031/0.068
	–	Fixed, red	230 V ~	Yellow	1	ZBY9W2M140	0.031/0.068
	EMERGENCY STOP	Fixed, red + white	24 V ~	Yellow	1	ZBY9W3B330	0.031/0.068
	ARRET D'URGENCE	Fixed, red + white	24 V ~	Yellow	1	ZBY9W3B130	0.031/0.068
NOT HALT	Fixed, red + white	24 V ~	Yellow	1	ZBY9W3B230	0.031/0.068	
PARADA DE EMERGENCIA	Fixed, red + white	24 V ~	Yellow	1	ZBY9W3B430	0.031/0.068	
ARRESTO DI EMERGENZA	Fixed, red + white	24 V ~	Yellow	1	ZBY9W3B630	0.031/0.068	
–	Fixed, red + white	24 V ~	Yellow	1	ZBY9W3B140	0.031/0.068	




ZBY9W2B330



ZBY9W3B140

(1) For compliance with standard EN/ISO 13850, paragraph 4.4.6, the Emergency Stop function logo  has been added.

(2) Compatible only with XALKW01.



ZBZ160●



ZBZ1605

Accessories for mushroom head pushbuttons (continued)

Description	Exclusive use with the following Ø 40 mm/1.575 in. trigger action pushbuttons	Color	Reference	Weight kg/lb
Metal guards for Emergency stop function, padlockable (1)	XB5AT8● XB5AS8● XB5AS9● ZB5AT8● ZB5AS8● ZB5AS9●	Chromium plated	ZBZ1600	0.046/0.101
		Black	ZBZ1602	0.046/0.101
		Red	ZBZ1604	0.046/0.101
		Yellow	ZBZ1605	0.046/0.101
		Blue	ZBZ1606	0.046/0.101

Circular yellow legends for metal guard ZBZ16●● (2)

Description	Marking	Color	Sold in lots of	Reference	Weight kg/lb
For Emergency stop function					
Ø 60 mm/2.362 in. legend for metal guard ZBZ16●●	Without	Yellow	10	ZBY9140M	0.004/0.009
	ARRET D'URGENCE	Yellow	10	ZBY9130M	0.004/0.009
	EMERGENCY STOP	Yellow	10	ZBY9330M	0.004/0.009
	NOT-HALT	Yellow	10	ZBY9230M	0.004/0.009
	PARADA DE EMERGENZA	Yellow	10	ZBY9430M	0.004/0.009
	NOODSTOP	Yellow	10	ZBY9530M	0.004/0.009
	ARRESTO DI EMERGENZA	Yellow	10	ZBY9630M	0.004/0.009
	NODSTOPP	Yellow	10	ZBY9730M	0.004/0.009
	NODSTOP	Yellow	10	ZBY9830M	0.004/0.009
For Emergency switching off function					
Ø 60 mm/2.362 in. legend for metal guard ZBZ16●●	Without	Yellow	10	ZBY9101M	0.004/0.009
	COUPURE D'URGENCE	Yellow	10	ZBY9160M	0.004/0.009
	EMERGENCY SWITCHING OFF	Yellow	10	ZBY9360M	0.004/0.009
	NOT-AUS	Yellow	10	ZBY9260M	0.004/0.009
	DESCONEXION DE EMERGENCIA	Yellow	10	ZBY9460M	0.004/0.009




ZBY9330M



ZBY9360M

(1) No isolation function is possible when this guard is fitted.

(2) To add customized markings on these references through web customization tool, see page 7.



ZBZ3605

Accessories for mushroom head pushbuttons (5)

Description	Exclusive use with the following Ø 40 mm/1.575 in. trigger action pushbuttons	Color	Reference	Weight kg/lb
Padlocking kit (1) (2) for Emergency stop (3) and Emergency switching off function (4), (padlockable)	XB5AS844● XB5AS944● ZB5AS844 ZB5AS944●	Yellow	ZBZ3605	0.045/0.099

Description	Marking	Color	Reference	Weight kg/lb
Ø 60 mm/2.363 in. legend for padlocking device ZBZ3605 for Emergency stop function (3)	—	Yellow	ZBY9140T	0.004/0.009
	ARRET D'URGENCE	Yellow	ZBY9130T	0.004/0.009
	EMERGENCY STOP	Yellow	ZBY9330T	0.004/0.009
	NOT-HALT	Yellow	ZBY9230T	0.004/0.009



ZBY9330T

(1) Standard circular legends are not compatible with this product. Use special legends [ZBY9●●●T](#).

(2) No isolation function is possible when this guard is fitted.

(3) For conformity with standards EN/IEC 60204-1 and EN/ISO 13850.

(4) For conformity with standard EN/IEC 60204-1.

(5) To add customized markings on these references using the web customization tool, see [page 7](#).

Control stations and enclosures

Plastic control stations XALD and XALK

For Harmony XB5 control and signaling units Ø 22

Stations for customer assembly: accessories



ZBA3

Pushbutton caps - unmarked (1)

For use with	Cap	Color	Sold in lots of	Unit reference	Weight kg/lb
	Type				
Circular pushbutton heads ZB5AA supplied without cap	Flush	White	10	ZBA1	0.001/0.002
		Black	10	ZBA2	0.001/0.002
		Green	10	ZBA3	0.001/0.002
		Red	10	ZBA4	0.001/0.002
		Yellow	10	ZBA5	0.001/0.002
		Blue	10	ZBA6	0.001/0.002



ZBL4

Pushbutton caps - marked (sold in lots of 10)

For use with	Type of push	Marking	Color of cap	Unit reference	Weight kg/lb	
		Text Color				
Circular pushbutton heads ZB5AA supplied without cap	Flush	I	White	Green	ZBA331	0.001/0.002
			Black	White	ZBA131	0.001/0.002
		II	White	Green	ZBA336	0.001/0.002
			White	Green	ZBA333	0.001/0.002
		⊕	White	Black	ZBA245	0.001/0.002
			Black	White	ZBA145	0.001/0.002
		UP	Black	White	ZBA343	0.001/0.002
		DOWN	White	Black	ZBA344	0.001/0.002
			White	Black	ZBA335	0.001/0.002
		↑	Black	White	ZBA334	0.001/0.002
			White	Red	ZBA432	0.001/0.002
		O	Black	Black	ZBA232	0.001/0.002
			White	Red	ZBA434	0.001/0.002
		STOP	Black	Black	ZBA234	0.001/0.002
			White	Red	ZBA435	0.001/0.002
		⬠	White	Green	ZBA346	0.001/0.002
		R	White	Blue	ZBA639	0.001/0.002
		+	White	Black	ZBA2934	0.001/0.002
		-	White	Black	ZBA2935	0.001/0.002

(1) To add customized markings on these references using the web customization tool, see page 7.



ZBA333



ZBV0133

Lens caps

Circular lens caps for light sources with Universal LED

Pilot lights	Color	Quantity	Reference	Weight
	White	10	ZBV0113	0.002/0.004
	Green	10	ZBV0133	0.002/0.004
	Red	10	ZBV0143	0.002/0.004
	Orange	10	ZBV0153	0.002/0.004
	Blue	10	ZBV0163	0.002/0.004



ZB5AZ905



ZB5SZ3



ZBZ58

Miscellaneous accessories

Description	For use with	Sold in lots of	Color	Unit reference	Weight kg/lb
Bezel tool	ZB5AZ901 head	10	–	ZB5AZ905	0.016/0.035
Nut	Fixing ZB5A head	10	Green	ZB5AZ903	0.002/0.004
Plastic blanking plugs (with fixing nut)	Square shape for Ø 22/0.866 in. units (1)	10	Black	ZB5SZ5	0.009/0.020
	Circular shape for Ø 22/0.866 in. units	10	Black	ZB5SZ3 (4)	0.009/0.020
Terminal branch	XALD and XALK control stations	10		XALZ09	0.003/0.007
Bellow seals (IP69K) (2)	Control station with 1 cut-out, installed in harsh environment + Emergency Stop pushbutton ZB5 (see 18)	2	Black	ZBZ28	0.009/0.020
			Yellow	ZBZ58	0.009/0.020

Replacement keys for Emergency stop key release heads and key switches

Description	Key number	Reference	Weight kg/lb
Set of 2 keys (3)	455	ZBG455	0.013/0.029
	421E	ZBG421E	0.014/0.031
	458A	ZBG458A	0.014/0.031
	520E	ZBG520E	0.014/0.031
	3131A	ZBG3131A	0.014/0.031



ZBG455

(1) Body/fixing collar **ZB5AZ009** necessary for fixation, to be ordered separately.

(2) Not compatible with Ø 30 mm/1.181 in. Emergency Stop heads.

(3) Other key numbers are available.

(4) To add customized markings on these references using the web customization tool, see [page 7](#).

X			
XALD01	13	XALK178	9
XALD01H7	13	XALK178E	9
XALD02	13	XALK178F	9
XALD02H7	13	XALK178FH29	9
XALD03	13	XALK178FH49	9
XALD03H7	13	XALK178G	9
XALD04	13	XALK178GTH26	9
XALD04H7	13	XALK178GTH29	9
XALD05	13	XALK178GTHFR	9
XALD05H7	13	XALK178W3B140E	10
XALD101	8	XALK178W3B140G	10
XALD101H29	8	XALK188	9
XALD102	8	XALK188E	9
XALD102E	8	XALK188F	9
XALD103	8	XALK188G	9
XALD104	8	XALK188GTH26	9
XALD112	8	XALK188W2B101G5	10
XALD112E	8	XALK198	9
XALD114	8	XALK84W2ME	10
XALD132	11	XALK84W2MG	10
XALD134	11	XALK84W3BE	10
XALD142	11	XALK84W3BG	10
XALD144	11	XALKW01	20
XALD144E	11	XALZ09	37
XALD164	8	XB5KS2B4	15
XALD164H29H7	8	XB5KS2B8	15
XALD211	11	XB5KS2G4	15
XALD211H29	11	XB5KS2G8	15
XALD213	11	XB5KS2M4	15
XALD213E	11	XB5KS2M8	15
XALD214	11	XB5KSB	15
XALD215	11	XB5KSG	15
XALD222	12	XB5KSM	15
XALD222E	12		
XALD223	12	Z	
XALD224	11	ZALVB1	14
XALD225	11	ZALVG1	14
XALD241	11	ZALVM1	14
XALD311	12	ZB5AA0	16
XALD311H29H7	12	ZB5AA1	16
XALD321	12	ZB5AA131	17
XALD321H29H7	12	ZB5AA131C0	17
XALD324	12	ZB5AA145	17
XALD324E	12	ZB5AA16	16
XALD325	12	ZB5AA16C0	16
XALD326	12	ZB5AA18	16
XALD328	12		27
XALD334	12	ZB5AA18C0	16
XALD339	12		27
XALD361B	11	ZB5AA1C0	16
XALD361M	11	ZB5AA2	16
XALD363B	11	ZB5AA232	17
XALD363G	11	ZB5AA234	17
XALD363M	11	ZB5AA245	17
XALK01	13	ZB5AA26	16
XALK01H29	13	ZB5AA26C0	16
XALK01HFR	13	ZB5AA2C0	16
XALK01TH26	13	ZB5AA3	16
XALK02	13	ZB5AA331	17
XALK03	13	ZB5AA331C0	17
XALK04	13	ZB5AA333	17
XALK05	13	ZB5AA333C0	17
		ZB5AA334	17
		ZB5AA334C0	17
		ZB5AA335	17
		ZB5AA335C0	17
		ZB5AA336	17
		ZB5AA341	17
		ZB5AA342	17
		ZB5AA343	17
		ZB5AA344	17
		ZB5AA36	16
		ZB5AA36C0	16
		ZB5AA38	16
		ZB5AA38C0	16
		ZB5AA3C0	16
		ZB5AA4	16
		ZB5AA432	17
		ZB5AA432C0	17
		ZB5AA433	17
		ZB5AA434	17
		ZB5AA434C0	17
		ZB5AA435	17
		ZB5AA46	16
		ZB5AA46C0	16
		ZB5AA48	16
		ZB5AA48C0	16
		ZB5AA4C0	16
		ZB5AA5	16
		ZB5AA56	16
		ZB5AA56C0	16
		ZB5AA58	16
			27
		ZB5AA58C0	16
		ZB5AA5C0	16
		ZB5AA6	16
		ZB5AA66	16
		ZB5AA66C0	16
		ZB5AA68	16
			27
		ZB5AA68C0	16
			27
		ZB5AA6C0	16
		ZB5AA8	16
		ZB5AA88	27
		ZB5AA88C0	27
		ZB5AA8C0	16
		ZB5AA9	16
		ZB5AC2	17
		ZB5AC24	17
		ZB5AC3	17
		ZB5AC34	17
		ZB5AC4	17
		ZB5AC44	17
		ZB5AC5	17
		ZB5AC54	17
		ZB5AC6	17
		ZB5AC64	17
		ZB5AD2	23
		ZB5AD201	23
		ZB5AD201C0	23
		ZB5AD203	23
		ZB5AD203C0	23
		ZB5AD204	24
		ZB5AD204C0	24
		ZB5AD205	24
		ZB5AD205C0	24
		ZB5AD206	24
		ZB5AD28	26
		ZB5AD2801	26
		ZB5AD2801C0	26
		ZB5AD2804	26
		ZB5AD2804C0	26
		ZB5AD2806C0	26
		ZB5AD28C0	26
		ZB5AD29	25
		ZB5AD29C0	25
		ZB5AD2C0	23
		ZB5AD3	23
		ZB5AD301	23
		ZB5AD301C0	23
		ZB5AD303	23
		ZB5AD303C0	23
		ZB5AD304	24
		ZB5AD304C0	24
		ZB5AD305	24
		ZB5AD306	24
		ZB5AD39	25
		ZB5AD39C0	25
		ZB5AD3C0	23
		ZB5AD4	23
		ZB5AD401C0	23
		ZB5AD403C0	23
		ZB5AD404C0	24
		ZB5AD405C0	24
		ZB5AD406	24
		ZB5AD48C0	26
		ZB5AD49C0	25
		ZB5AD4C0	23
		ZB5AD5	23
		ZB5AD501	23
		ZB5AD501C0	23
		ZB5AD503	23
		ZB5AD503C0	23
		ZB5AD504C0	24
		ZB5AD505	24
		ZB5AD506	24
		ZB5AD59	25
		ZB5AD59C0	25
		ZB5AD5C0	23
		ZB5AD7	23
		ZB5AD701C0	23
		ZB5AD703C0	23
		ZB5AD704C0	24
		ZB5AD705	24
		ZB5AD706	24
		ZB5AD79C0	25
		ZB5AD7C0	23
		ZB5AD8	23
		ZB5AD801C0	23
		ZB5AD803C0	23
		ZB5AD804C0	24
		ZB5AD805	24
		ZB5AD806	24
		ZB5AD89C0	25
		ZB5AD8C0	23
		ZB5AG0	25
		ZB5AG02	25
		ZB5AG02D	26
		ZB5AG03D	26
		ZB5AG05	25
		ZB5AG05C0	25
		ZB5AG07D	26
		ZB5AG08	25
		ZB5AG08C0	25
		ZB5AG09	25
		ZB5AG0C0	25
		ZB5AG0D	26
		ZB5AG1	25
		ZB5AG2	25
		ZB5AG2C0	25
		ZB5AG2D	26
		ZB5AG2DC0	26
		ZB5AG3	25
		ZB5AG3C0	25
		ZB5AG3D	26
		ZB5AG4	25
		ZB5AG4C0	25
		ZB5AG4D	26
		ZB5AG4DC0	26
		ZB5AG5	25
		ZB5AG6	25
		ZB5AG6C0	25
		ZB5AG6D	26
		ZB5AG7	25
		ZB5AG7C0	25
		ZB5AG7D	26
		ZB5AG8	25
		ZB5AG9	25
		ZB5AG9C0	25
		ZB5AJ2	24
		ZB5AJ2C0	24
		ZB5AJ3	24
		ZB5AJ3C0	24
		ZB5AJ4	24
		ZB5AJ4C0	24
		ZB5AJ5	24
		ZB5AJ5C0	24
		ZB5AJ7	24
		ZB5AJ7C0	24
		ZB5AJ8	24
		ZB5AJ8C0	24
		ZB5AK1213	28
		ZB5AK1213C0	28
		ZB5AK1233	28
		ZB5AK1233C0	28
		ZB5AK1243	28
		ZB5AK1243C0	28
		ZB5AK1253	28
		ZB5AK1253C0	28
		ZB5AK1263	28
		ZB5AK1263C0	28
		ZB5AK1283	28
		ZB5AK1283C0	28
		ZB5AK1313	28
		ZB5AK1313C0	28
		ZB5AK1333	28

ZB5AK1333C0	28	ZB5AL3C0	16	ZB5AW113	27	ZBA344	36	ZBY2179	29
ZB5AK1343	28	ZB5AL4	16	ZB5AW113C0	27	ZBA346	36	ZBY2185	29
ZB5AK1343C0	28	ZB5AL432	17	ZB5AW133	27	ZBA4	36	ZBY2186	29
ZB5AK1353	28	ZB5AL432C0	17	ZB5AW133C0	27	ZBA432	36	ZBY2186C0	29
ZB5AK1353C0	28	ZB5AL434	17	ZB5AW143	27	ZBA434	36	ZBY2195	29
ZB5AK1363	28	ZB5AL4C0	16	ZB5AW143C0	27	ZBA435	36	ZBY2303	30
ZB5AK1363C0	28	ZB5AL5	16	ZB5AW153	27	ZBA5	36	ZBY2303C0	30
ZB5AK1383	28	ZB5AL5C0	16	ZB5AW153C0	27	ZBA6	36	ZBY2304	29
ZB5AK1383C0	28	ZB5AL6	16	ZB5AW163	27	ZBA639	36	ZBY2304C0	29
ZB5AK1413	28	ZB5AL6C0	16	ZB5AW163C0	27	ZBCZ34	29	ZBY2305	30
ZB5AK1413C0	28	ZB5AP1S	16	ZB5AW183	27	ZBE101	14	ZBY2306	30
ZB5AK1433	28	ZB5AP2S	16	ZB5AW313	27	ZBE1015	14	ZBY2311	30
ZB5AK1433C0	28	ZB5AP3S	16	ZB5AW313C0	27	ZBE102	14	ZBY2312	30
ZB5AK1443	28	ZB5AP4S	16	ZB5AW313S	27	ZBE1025	14	ZBY2313	30
ZB5AK1443C0	28	ZB5AP5S	16	ZB5AW313SC0	27	ZBE302	14	ZBY2314	30
ZB5AK1453	28	ZB5AP6S	16	ZB5AW333	27	ZBG3131A	37	ZBY2322	30
ZB5AK1453C0	28	ZB5AS12	18	ZB5AW333C0	27	ZBG421E	37	ZBY2323	30
ZB5AK1463	28	ZB5AS42	18	ZB5AW333S	27	ZBG455	37	ZBY2326	30
ZB5AK1463C0	28	ZB5AS52	18	ZB5AW333SC0	27	ZBG458A	37	ZBY2330	30
ZB5AK1483	28	ZB5AS55	18	ZB5AW343	27	ZBG520E	37	ZBY2334	30
ZB5AK1483C0	28	ZB5AS62	18	ZB5AW343C0	27	ZBV0113	37	ZBY2364	30
ZB5AK1513	28	ZB5AS72	18	ZB5AW343S	27	ZBV0133	37	ZBY2366	30
ZB5AK1513C0	28	ZB5AS834	19	ZB5AW343SC0	27	ZBV0143	37	ZBY2367	30
ZB5AK1533	28	ZB5AS842Y	22	ZB5AW353	27	ZBV0153	37	ZBY2367C0	30
ZB5AK1533C0	28	ZB5AS844	19	ZB5AW353C0	27	ZBV0163	37	ZBY2385	30
ZB5AK1543	28	ZB5AS84W00	20	ZB5AW353S	27	ZBVB1	14	ZBY2H101	29
ZB5AK1543C0	28	ZB5AS84W2B	20	ZB5AW353SC0	27	ZBVB15	14	ZBY4100	31
ZB5AK1553	28	ZB5AS84W2G	20	ZB5AW363	27	ZBVG1	14	ZBY4101	29
ZB5AK1553C0	28	ZB5AS84W2M	20	ZB5AW363C0	27	ZBVG15	14	ZBY4101C0	29
ZB5AK1563	28	ZB5AS84W3B	20	ZB5AW363S	27	ZBVM1	14	ZBY4H101	29
ZB5AK1563C0	28	ZB5AS934	19	ZB5AW363SC0	27	ZBVM15	14	ZBY9101	21
ZB5AK1583	28	ZB5AS944	19	ZB5AW383	27	ZBY0101	31	ZBY9101M	34
ZB5AK1583C0	28	ZB5AS944D	19	ZB5AW383C0	27	ZBY0102	31	ZBY9120	19
ZB5AK1713	28	ZB5AS964	19	ZB5AW383S	27	ZBY0123	29		32
ZB5AK1713C0	28	ZB5AT2	18	ZB5AW383SC0	27	ZBY02103	31	ZBY9121	19
ZB5AK1733	28	ZB5AT24	18	ZB5AW713	18	ZBY02126	31		32
ZB5AK1733C0	28	ZB5AT84	19	ZB5AW733	18	ZBY02178	31	ZBY9130M	34
ZB5AK1743	28	ZB5AT844	19	ZB5AW743	21	ZBY02185	31	ZBY9130T	35
ZB5AK1743C0	28	ZB5AT8643M	21	ZB5AW753	18	ZBY02304	31	ZBY9140M	34
ZB5AK1753	28	ZB5AT8643M130	21	ZB5AW763	18	ZBY1101	32	ZBY9140T	35
ZB5AK1753C0	28	ZB5AT8643M140	21	ZB5AX2	18	ZBY1147	32	ZBY9160	21
ZB5AK1763	28	ZB5AT8643M230	21	ZB5AX84	19	ZBY2101	29		32
ZB5AK1763C0	28	ZB5AT8643M330	21	ZB5A2009	14	ZBY2101C0	29	ZBY9160M	34
ZB5AK1783	28	ZB5AT8643M430	21	ZB5AZ903	37	ZBY2103	29	ZBY9220	19
ZB5AK1783C0	28	ZB5AT8643M630	21	ZB5AZ905	37	ZBY2103C0	29		32
ZB5AK1813	28	ZB5AV013	27	ZB5SZ3	37	ZBY2104	29	ZBY9230M	34
ZB5AK1813C0	28	ZB5AV013E	27	ZB5SZ5	37	ZBY2104C0	29	ZBY9230T	35
ZB5AK1833	28	ZB5AV013S	27	ZBA1	36	ZBY2107	29	ZBY9260	21
ZB5AK1833C0	28	ZB5AV033	27	ZBA131	36	ZBY2108	29		32
ZB5AK1843	28	ZB5AV033E	27	ZBA145	36	ZBY2111	29	ZBY9260M	34
ZB5AK1843C0	28	ZB5AV033S	27	ZBA2	36	ZBY2113	29	ZBY9320	19
ZB5AK1853	28	ZB5AV043	27	ZBA232	36	ZBY2114	29		32
ZB5AK1853C0	28	ZB5AV043E	27	ZBA234	36	ZBY2123	29	ZBY9330M	34
ZB5AK1863	28	ZB5AV043S	27	ZBA245	36	ZBY2126	29	ZBY9330T	35
ZB5AK1863C0	28	ZB5AV053	27	ZBA2934	36	ZBY2130	29	ZBY9360	21
ZB5AK1883	28	ZB5AV053E	27	ZBA2935	36	ZBY2134	29		32
ZB5AK1883C0	28	ZB5AV053S	27	ZBA3	36	ZBY2135	29	ZBY9360M	34
ZB5AL1	16	ZB5AV063	27	ZBA331	36	ZBY2147	29	ZBY9420	19
ZB5AL1C0	16	ZB5AV063E	27	ZBA333	36	ZBY2164	29		32
ZB5AL2	16	ZB5AV063S	27	ZBA334	36	ZBY2166	29	ZBY9430M	34
ZB5AL232	17	ZB5AV083	27	ZBA335	36	ZBY2166C0	29	ZBY9460M	34
ZB5AL2C0	16	ZB5AV083E	27	ZBA336	36	ZBY2178	29	ZBY9530M	34
ZB5AL3	16	ZB5AV083S	27	ZBA343	36	ZBY2178C0	29		

ZBY9620	19
	32
ZBY9630M	34
ZBY9730M	34
ZBY9830M	34
ZBY9W2B130	19
	33
ZBY9W2B140	33
ZBY9W2B230	19
	33
ZBY9W2B330	19
	33
ZBY9W2B430	33
ZBY9W2B630	33
ZBY9W2G130	33
ZBY9W2G140	33
ZBY9W2G230	33
ZBY9W2G330	33
ZBY9W2G430	33
ZBY9W2G630	33
ZBY9W2M130	33
ZBY9W2M140	33
ZBY9W2M230	33
ZBY9W2M330	33
ZBY9W2M430	33
ZBY9W2M630	33
ZBY9W3B130	33
ZBY9W3B140	33
ZBY9W3B230	33
ZBY9W3B330	33
ZBY9W3B430	33
ZBY9W3B630	33
ZBZ1600	34
ZBZ1602	34
ZBZ1604	34
ZBZ1605	34
ZBZ1606	34
ZBZ28	22
	37
ZBZ32	29
ZBZ32C0	29
ZBZ34	29
ZBZ3605	35
ZBZ58	22
	37
ZENL1111	14
ZENL1121	14

mySchneider, your personalized digital experience

Access an all-in-one customized online experience and benefit from tailored business services, resources, and tools to efficiently support your business operations.

- **Efficiency:** In just a few clicks, find all the information and support you need to get the job done.
- **Simplicity:** Use a single login to access all business services, in one place, available 24/7. You no longer need to log in to multiple platforms.
- **Personalization:** Benefit from content, tools, and business services tailored to your activity, and customize your landing page based on your preferences.

Watch the How-to Videos



Order management

- > [Select Products and Add to Cart](#)
- > [Check for Products' Price and Availability](#)
- > [Order Products with Generic Commercial References](#)




Product information

- > [Find a Product Data Sheet and Related Documents](#)
- > [Select Products and Add to Cart](#)
- > [Stay Up to Date on the Status of My Products](#)



Support

- > [Get Quicker Answers Thanks to Online Support](#)



Training

- > [Access Trainings Dedicated to My Activity](#)

[Create your account](#)

Life Is 

Schneider
Electric

Legal information

The information provided in this Catalog contains description of Schneider Electric products, solutions and services ("Offer") with technical specifications and technical characteristics of the performance of the corresponding Offer.

The content of this document is subject to revision at any time without notice due to continued progress in methodology, design and manufacturing.

To the extent permitted by applicable law, no responsibility or liability is assumed by Schneider Electric and its subsidiaries for any type of damages arising out of or in connection with (i) informational content of this Catalog not conforming with or exceeding the technical specifications, or (ii) any error contained in this Catalog, or (iii) any use, decision, act or omission made or taken on basis of or in reliance on any information contained or referred to in this Catalog.


SCHNEIDER ELECTRIC MAKES NO WARRANTY OR REPRESENTATION OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO WHETHER THIS CATALOG OR ANY INFORMATION CONTAINED THEREIN SUCH AS PRODUCTS AND SERVICES WILL MEET REQUIREMENTS, EXPECTATIONS OR PURPOSE OF ANY PERSON MAKING USE THEREOF.

Schneider Electric brand and any trademarks of Schneider Electric and its subsidiaries referred to in this Catalog are property of Schneider Electric or its subsidiaries. All other brands are trademarks of their respective owners.

This Catalog and its content are protected under applicable copyright laws and provided for informative use only. No part of this Catalog may be reproduced or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), for any purpose, without the prior written permission of Schneider Electric.

Copyright, intellectual, and all other proprietary rights in the content of this Catalog (including but not limited to software, audio, video, text, and photographs) rests with Schneider Electric or its licensors. All rights in such content not expressly granted herein are reserved. No rights of any kind are licensed or assigned or shall otherwise pass to persons accessing this information.

Life Is On



Learn more about our products at www.se.com

Design: Schneider Electric
Photos: Schneider Electric

Schneider Electric Industries SAS

Head Office
35, rue Joseph Monier - CS 30323
F-92500 Rueil-Malmaison Cedex
France

DIA5ED2130508EN
January 2026 - V6.0