



Overview

Safety

Overview

Safety

Compact safety magnetic sensors



		MC36CH_M5	MC36CH_A2	MC36CH_T1	MC88CH_M5	MC88CH_A2	MC88CH_T1
Switching distance	Sao: 5mm; Sar: 15mm	With MC36CM			With MC88CM1		
	Sao: 8mm; Sar: 18mm				With MC88CM2		
	Sao: 18mm; Sar: 30mm				With MC88CM3		
	Sao: 15mm; Sar: 20mm						
	Sao: 16 mm; Sar: 20mm						
Connection type	M8 plug left exit	▼			▼		
	M8 plug right exit	▼			▼		
	Cable left exit		▼			▼	
	Cable right exit		▼			▼	
	Pigtail M12 left exit			▼			▼
	Pigtail M12 right exit			▼			▼
	Cable						
Reed switch outputs	1 NO						
	1 NC + 1 NO	▼	▼	▼	▼	▼	▼
	2 NO	▼	▼	▼	▼	▼	▼
	2 NO + 1 NC		▼			▼	
LED indication	With LED		▼			▼	
	No LED		▼			▼	
Safety parameters	Electrical life cycle	700.000 operations @ 250 mA resistive load					
	B10d (for each channel)	80.000.000 of operations					
Environmental	Operating temperature	-25° to +80°C (-13° to +176°F)					
	Protection degree	IP67 with LED IP69K without LED	IP67	IP67	IP67 with LED IP69K without LED	IP67	IP67
Electrical data	Switching voltage	12-24 VAC/DC					
	Switching current	250 mA	250 mA	250 mA	250 mA	250 mA	250 mA
	Switching power	6 W	6 W	6 W	6 W	6 W	6 W
Housing	Style	Cubic - miniature			Cubic - standard		
	Length	36 mm / 1,41"			88 mm / 3,46"		
	Width	26 mm / 1,02"			25 mm / 0,98"		
	Height	13 mm / 0,51"			13 mm / 0,51"		
	Diameter						
	Material	PBT			PBT		
Actuator	MC36CM		▼				
	MC88CM1, MC88CM2, MC88CM3					▼	
	CLSA2 (for M18)						
	CLSA3 (for M30)						
Approvals		CE, cULus	CE, cULus	CE, cULus	CE, cULus	CE, cULus	CE, cULus

Safety magnetic sensors



		SMSA2P10	SMSA2P02	SMSA3P02	SMSA2P03
Switching distance	Sao: 5mm; Sar: 15mm				
	Sao: 8mm; Sar: 18mm				
	Sao: 18mm; Sar: 30mm				
	Sao: 15mm; Sar: 20mm		With CLSA2	With CLSA3	
	Sao: 16 mm; Sar: 20mm	With CLSA2			With CLSA2
Connection type	M8 plug left exit				
	M8 plug right exit				
	Cable left exit				
	Cable right exit				
	Pigtail M12 left exit				
	Pigtail M12 right exit				
	Cable	▼	▼	▼	▼
Reed switch outputs	1 NO	▼			
	1 NC + 1 NO		▼	▼	
	2 NO				▼
	2 NO + 1 NC				
LED indication	With LED		(on request)		
	No LED	▼	▼	▼	▼
Safety parameters	Electrical life cycle				
	B10d (for each channel)				
Environmental	Operating temperature	-25° to +70°C (-13° to +158°F)			
	Protection degree	IP67	IP67	IP67	IP67
Electrical data * CE version	Switching voltage	100 VAC			
	Switching current	250 mA	250 mA	250 mA	250 mA
	Switching power	5 VA	5 VA	5 VA	5 VA
Housing	Style	Cylindrical			
	Length	38 mm / 1,49"	38 mm / 1,49"	42 mm / 1,65"	38 mm / 1,49"
	Width				
	Height				
	Diameter	M18 x 1	M18 x 1	M30 x 1.5	M18 x 1
	Material	PBT			
	MC36CM				
Actuator	MC88CM1, MC88CM2, MC88CM3				
	CLSA2	▼	▼		▼
	CLSA3			▼	
Approvals		CE	CE (UL on request)	CE	CE

Overview

Safety

Safety modules



		SMS20	SMS31	SMSA31	SM2H21	SME41
Safety functions	Emergency stop	▼	▼			
	Safety magnetic switch	▼	▼	▼		
	Safety limit switch	▼	▼	▼		
	Safety hinge	▼	▼	▼		
	Electromechanical interlock	▼	▼			
	Lift levelling	▼	▼			
	Two-hand controls				▼	
	ESPE type 2					
	ESPE type 4					
	Safety mats					
	Expansion relay unit	in combination with SME41				▼
Safety outputs	NO relay outputs	2	3	3	2	4
	OSSD delayed outputs					
	OSSD instantaneous outputs					
Auxiliary outputs	NC relay outputs		1	1	1	1
	OSSD outputs					
	PNP output				1	
Start mode	Manual	▼	▼	▼		
	Automatic	▼	▼	▼		
	Monitored manual	▼	▼	▼		
Connection type	Pluggable screw terminals	▼	▼	▼	▼	▼
	Fix screw terminals					
Safety parameters	Safety	Cat. 4 - PL e as EN ISO 13849				
	MTTFD	420,8	420,8	420,8	422,1	363,4
	PFHD	1,85 E-10	1,85 E-10	1,85 E-10	1,35 E-10	1,59 E-10
	DCavg	99%	99%	99%	99%	99%
Power supply	24 VDC/AC	▼	▼	▼	▼	▼
Dimensions	Width	17,5 mm / 0,69"				
	Height	110,8 mm / 4,36"				
	Depth	121,1 mm / 4,77"				
Approvals		CE, UL, TÜV, RoHS EN 81-20, EN 81-50	CE, UL, TÜV, RoHS EN 81-20, EN 81-50	CE, TÜV, cULus, RoHS	CE, TÜV, cULus, RoHS	CE, TÜV, cULus, RoHS

Safety modules



		CM22D0A	CM30D1A	CM40D0A
Safety functions	Emergency stop	▼	▼	▼
	Safety magnetic switch	▼	▼	▼
	Safety limit switch	▼	▼	▼
	Safety hinge	▼	▼	▼
	Electromechanical interlock	▼	▼	▼
	Lift levelling			
	Two-hand controls			
	ESPE type 2	▼	▼	▼
	ESPE type 4	▼	▼	▼
	Safety mats	▼	▼	▼
	Expansion relay unit	in combination with SME41		
Safety outputs	NO relay outputs			
	OSSD delayed outputs	2 / -		
	OSSD instantaneous outputs	2 / 3 / 4	3	4
Auxiliary outputs	NC relay outputs	-	-	
	OSSD outputs	- / 1 / -	1	
	PNP output			
Start mode	Manual	▼	▼	▼
	Automatic	▼	▼	▼
	Monitored manual	▼	▼	▼
Connection type	Pluggable screw terminals			
	Fix screw terminals	▼	▼	▼
Safety parameters	Safety	Cat. 4 - PL e as EN 13849 / SIL3 as IEC 61508 / SILCL3 as IEC 62061		
	MTTFD	2403	2403	2403
	PFHD	1,89 E-09	1,89 E-09	1,89 E-09
	DCavg	99%	99%	99%
Power supply	24 VDC	▼	▼	▼
Dimensions	Width	17,5 mm / 0,69"		
	Height	90 mm / 3,54"		
	Depth	63 mm / 2,48"		
Approvals		CE, TÜV, cULus, RoHS	CE, TÜV, cULus, RoHS	CE, TÜV, cULus, RoHS

Overview

Safety

Limit switches - Safety hinge - E

							
		PS21S	PS21H	PS21R	PS31S	PS31R	PS31P
Actuation	External actuator key	▼			▼		
	External hinge		▼				
	Hinge mount						
	Pull wire			▼		▼	
	Electromagnetic interlock						
Reset	No reset			▼		▼	
	Manual reset			▼		▼	
Interlock	Electrical						
	Mechanical						
Contact outputs	1 NC + 1 NO	▼	▼	▼	▼	▼	
	2 NC	▼	▼	▼	▼	▼	
	2 NC + 1 NO				▼	▼	
	2 NC + 2 NO						
	1 NC + 2 NO				▼	▼	
	3 NC				▼	▼	
	3 NC + 1 NO						
	2 NC operated by solenoid						
	1 NO operated by solenoid						
	1 NO operated by key						
	1 NC operated by key						
Rated operational current	I _e /AC-15 230 VAC						3,1 A
	I _e /DC-13 24 VDC						2,8 A
Safety parameters	Mechanical durability						1.000.000 of operations
	B10d						2.000.000 of operations
Housing	Width	30 mm / 1,18"			40 mm / 1,57"		
	Plastic	▼	▼				
	Metal			▼	▼	▼	
	Protection degree	IP65	IP65	IP66	IP66	IP66	
Approvals		CE, UL, CSA, RoHS	CE, UL, CSA, RoHS	CE, UL, CSA, RoHS	CE, UL, CSA, RoHS	CE, UL, CSA, RoHS	CE, UL, CSA, RoHS

Electromagnetic safety interlock

							
PS42S	PS42R	PS43S	PS43R	PS38H_T1	PS38H_T2	ESI_E	ESI_M
▼		▼				▼	▼
				▼	▼		
	▼		▼				
	▼		▼				
	▼		▼			▼	
							▼
▼	▼	▼	▼				
▼	▼	▼	▼				
		▼	▼		▼		
		▼	▼				
		▼	▼	▼			
						ESI1	ESI1
						ESI2	ESI2
						ESI3	ESI3
						ESI1	ESI1
						ESI2	ESI2
						ESI3	ESI3
						ESI1	ESI1
						ESI2	ESI2
						ESI3	ESI3
				4 A		4 A	4 A
				2 A		4 A	4 A
				1.000.000 of operations		1.000.000 of operations	
				2.000.000 of operations		4.000.000 of operations	
50 mm / 1,97"		60 mm / 2,36"		60 mm / 2,36"		40 mm / 1,57"	
▼	▼	▼	▼	▼	▼	▼	▼
IP66	IP66	IP66	IP66	IP67		IP65	
CE, UL, CSA, RoHS	CE, UL, CSA, RoHS	CE, UL, CSA, RoHS	CE, UL, CSA, RoHS	CE, UL, CSA, RoHS		CE, cULus, IMQ, RoHS	

OUR SALES NETWORK IN EUROPE

AUSTRIA

Carlo Gavazzi GmbH
Ketzergergasse 374,
A-1230 Wien
Tel: +43 1 888 4112
Fax: +43 1 889 1053
office@carlo gavazzi.at

BELGIUM

Carlo Gavazzi NV/SA
Mechelsesteenweg 311,
B-1800 Vilvoorde
Tel: +32 2 257 41 20
sales@carlo gavazzi.be

DENMARK

Carlo Gavazzi Handel A/S
Over Hadstenvej 40,
DK-8370 Hadsten
Tel: +45 89 60 61 00
Fax: +45 86 98 15 30
handel@carlo gavazzi.dk

FINLAND

Carlo Gavazzi OY AB
Ahventie, 4 B
FI-02170 Espoo
Tel: +358 9 756 2000
myynti@carlo gavazzi.fi

FRANCE

Carlo Gavazzi Sarl
Zac de Paris Nord II, 69, rue de la Belle Etoile,
F-95956 Roissy CDG Cedex
Tel: +33 1 49 38 98 60
Fax: +33 1 48 63 27 43
french.team@carlo gavazzi.fr

GERMANY

Carlo Gavazzi GmbH
Pfnorstr. 10-14
D-64293 Darmstadt
Tel: +49 6151 81 00 0
Fax: +49 6151 81 00 40
info@carlo gavazzi.de

GREAT BRITAIN

Carlo Gavazzi UK Ltd
4.4 Frimley Business Park,
Frimley, Camberley, Surrey GU16 7SG
Tel: +44 1 276 854110
Fax: +44 1 276 682140
sales@carlo gavazzi.co.uk

ITALY

Carlo Gavazzi SpA
Via Milano 13,
I-20045 Lainate
Tel: +39 02 931 76 1
Fax: +39 02 931 76 301
info@carlo gavazziacbu.it

NETHERLANDS

Carlo Gavazzi BV
Wijkmeerweg 23,
NL-1948 NT Beverwijk
Tel: +31 251 22 93 45
info@carlo gavazzi.nl

NORWAY

Carlo Gavazzi AS
Melkeveien 13,
N-3919 Porsgrunn
Tel: +47 35 93 08 00
Fax: +47 35 93 08 01
post@carlo gavazzi.no

PORTUGAL

Carlo Gavazzi Lda
Rua dos Jerónimos 38-B,
P-1400-212 Lisboa
Tel: +351 21 361 70 60
Fax: +351 21 362 13 73
carlo gavazzi@carlo gavazzi.pt

SPAIN

Carlo Gavazzi SA
Avda. Iparraguirre, 80-82,
E-48940 Leioa (Bizkaia)
Tel: +34 94 480 40 37
Fax: +34 94 431 60 81
gavazzi@carlo gavazzi.es

SWEDEN

Carlo Gavazzi AB
V:a Kyrkogatan 1,
S-652 24 Karlstad
Tel: +46 54 85 11 25
Fax: +46 54 85 11 77
info@carlo gavazzi.se

SWITZERLAND

Carlo Gavazzi AG
Verkauf Schweiz/Vente Suisse
Sumpfstrasse 3,
CH-6312 Steinhausen
Tel: +41 41 747 45 35
Fax: +41 41 740 45 40
info@carlo gavazzi.ch

OUR SALES NETWORK IN THE AMERICAS

USA

Carlo Gavazzi Inc.
750 Hastings Lane,
Buffalo Grove, IL 60089-6904, USA
Tel: +1 847 465 61 00
Fax: +1 847 465 73 73
sales@carlo gavazzi.com

CANADA

Carlo Gavazzi Inc.
2660 Meadowvale Boulevard,
Mississauga, ON L5N 6M6, Canada
Tel: +1 905 542 0979
Fax: +1 905 542 2248
gavazzi@carlo gavazzi.com

MEXICO

Carlo Gavazzi Mexico S.A. de C.V.
Circuito Puericultores 22, Ciudad Satélite
Naucalpan de Juárez, Edo Mex. CP 53100
Mexico
T +52 55 5373 7042
F +52 55 5373 7042
mexicosales@carlo gavazzi.com

BRAZIL

Carlo Gavazzi Automação Ltda.
Av. Francisco Matarazzo, 1752
Conj 2108 05001-200 - São Paulo - SP
Tel: +55 11 3052 0832
Fax: +55 11 3057 1753
info@carlo gavazzi.com.br

OUR SALES NETWORK IN ASIA AND PACIFIC

SINGAPORE

Carlo Gavazzi Automation Singapore Pte. Ltd.
61 Tai Seng Avenue #05-06
Print Media Hub @ Paya Lebar iPark
Singapore 534167
Tel: +65 67 466 990
Fax: +65 67 461 980
info@carlo gavazzi.com.sg

MALAYSIA

Carlo Gavazzi Automation (M) SDN. BHD.
D12-06-G, Block D12,
Pusat Perdagangan Dana 1,
Jalan PJU 1A/46, 47301 - Petaling Jaya,
Selangor, Malaysia
Tel: +60 3 7842 7299
Fax: +60 3 7842 7399
info@carlo gavazzi-asia.com

CHINA

Carlo Gavazzi Automation
(China) Co. Ltd.
Unit 2308, 23/F.,
News Building, Block 1, 1002
Middle Shennan Zhong Road, Futian District,
Shenzhen, China
Tel: +86 755 8369 9500
Fax: +86 755 8369 9300
sales@carlo gavazzi.cn

HONG KONG

Carlo Gavazzi Automation
Hong Kong Ltd.
Unit No. 16 on 25th Floor, One Midtown,
No. 11 Hoi Shing Road, Tsuen Wan,
New Territories, Hong Kong
Tel: +852 26261332 / 26261333
Fax: +852 26261316

TAIWAN

Branch of Carlo Gavazzi Automation
Singapore Pte. Ltd.
22F-1, No.500 Shizheng Rd, Xitun Dist,
Taichung City 407,
Taiwan, China
Tel: +886 4 2258 4001
Fax: +886 4 2258 4002

OUR COMPETENCE CENTRES AND PRODUCTION SITES

DENMARK

Carlo Gavazzi Industri A/S
Hadsten

MALTA

Carlo Gavazzi Ltd
Zejtun

ITALY

Carlo Gavazzi Controls SpA
Belluno

LITHUANIA

Uab Carlo Gavazzi Industri Kaunas
Kaunas

CHINA

Carlo Gavazzi Automation (Kunshan) Co., Ltd.
Kunshan

HEADQUARTERS

Carlo Gavazzi Automation SpA
Via Milano, 13
I-20045 - Lainate (MI) - ITALY
Tel: +39 02 931 76 1
info@carlo gavazziautomation.com

Energy to Components!

www.gavazziautomation.com